### STATUTORY RULES OF NORTHERN IRELAND

# 2015 No. 406

## **CLEAN AIR**

# The Smoke Control Areas (Exempted Fireplaces) (Amendment No.2) Regulations (Northern Ireland) 2015

Made - - - - 9th December 2015

Coming into operation 31st January 2016

The Department of the Environment makes the following Regulations in exercise of the powers conferred by Article 17(7) of the Clean Air (Northern Ireland) Order 1981(1).

The Department is satisfied that the classes of fireplace set out in column 1 of the Schedule can, subject to the conditions set out in column 2 of the Schedule, be used for burning fuel other than authorised fuels(2) without producing any smoke or a substantial quantity of smoke.

#### Citation commencement and interpretation

- 1.—(1) These Regulations may be cited as the Smoke Control Areas (Exempted Fireplaces) (Amendment No.2) Regulations (Northern Ireland) 2015 and come into operation on 31st January 2016
- (2) In these Regulations, "the Principal Regulations" mean the Smoke Control Areas (Exempted Fireplaces) (No.2) Regulations (Northern Ireland) 2013(3).

### **Amendments to the Principal Regulations**

- **2.**—(1) The Schedule to the Principal Regulations is amended in accordance with paragraphs (2) to (5).
- (2) The classes of fireplace described in the first column under the heading "(1) Class of fireplace" beginning with the words—
  - (a) "Rais Juno";
  - (b) "RAIS VIVA 98";
  - (c) "Sherborne SE NS-3C, Chesham SE NS-3B, Burford SE NS-3A"; and
  - (d) "Vista Magnifico SE NS-1 and Vista Perfetto SE NS-2";

<sup>(1)</sup> S.I. 1981/158 (N.I. 4), to which there are amendments not relevant to these Regulations.

<sup>(2)</sup> Fuels declared by the Department of the Environment to be authorised fuels for the purposes of Article 2(2) of the Clean Air (Northern Ireland) Order 1981 are specified in S.R. 2013 No. 205, as amended by S.R. 2014 No. 249.

<sup>(3)</sup> S.R. 2013 No. 292, as amended by S.R. 2014 No. 166, S.R. 2014 No. 294 and S.R. 2015 No. 274.

and the respective conditions set out in the second column under the heading "(2) Conditions" are omitted.

(3) In the class of fireplace described in the first column under the heading "(1) Class of fireplace" beginning with the word—

"Senza",

for the words "Senza UK w/o sideglass and Senza UK w/ sideglass", substitute the words "Senza UK with sideglass and Senza UK without sideglass".

- (4) In the classes of fireplace described in the first column under the heading "(1) Class of fireplace" beginning with the words—
  - (a) "Newbourne 40 and Newbourne 50 Freestanding stoves";
  - (b) "Newbourne 40 inset stove";
  - (c) "Pevex 60 convector stove";
  - (d) "Pevex Bohemia X 30, X 40, X 40 Cube, X 50 and X 60 multi-fuel stoves";
  - (e) "Pevex Bohemia X 40 Inset multi-fuel appliance";
  - (f) "Pevex Serenity 40D inset multi-fuel appliance";
  - (g) "Serenity 40 FS, Serenity 40 LS, Serenity 40 FW stoves";
  - (h) "Serenity 50FS, Serenity 50LS, Serenity 50FW and Serenity 50 Ped stoves"; and
  - (i) "Serenity 50 Inset stove",

for each time that they appear, for the address of the manufacturer ("Pevex Enterprises Ltd"), substitute "Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR".

(5) At the appropriate places in the Schedule, insert the classes of fireplace and the respective conditions set out in the Schedule to these Regulations.

Sealed with the Official Seal of the Department of the Environment on 9th December 2015.



Dave Foster
A senior officer of the
Department of the Environment

### SCHEDULE

 $Regulation\ 2$ 

(1) Class of fireplace	(2) Conditions	
буунершее	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Aarrow ECB5 Plus SC 5kW and ECB7 Plus SC 7kW wood- burning stoves manufactured by Arada Limited, The Fireworks, Weycroft Avenue, Axminster, Devon, EX13 5HU.	Operation & Installation manual dated July 2015 reference "ECB Plus SC Rev 06".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Aduro 16 5kW wood-burning stove manufactured by Aduro AS, Beringvej 17, DK-8361, Hasselager, Denmark.	Instruction manual dated July 2015 and reference "Version 1 – 2015.07".  The appliance must be fitted with a permanent stop to prevent closure of the secondary air slider beyond the 67% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Andalo 2, Lovero 2, Solaro 2 6.7 kW multifuel stoves manufactured by Drooff Kaminöfen GmbH & Co. KG, Keffelker Str. 40, D-59929 Brilon, Germany.	Instructions manual reference "Instructions: Installation, Operation, Function, Maintenance" and technical information dated July 2015 reference "Andalo 2-Lovero 2-Solaro 2, technical data" version SDK/0715.  The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Andorra model F9489,	Installation and Operation Manual dated 27th July 2015 reference "ANDORRA – Version A".	Wood logs. The fuel
Sevilla model F9489 V,	The appliance must be fitted with a modified air regulator which has a permanent opening of 620mm <sup>2</sup> when in the	must not contain halogenated
Delia model F9489 A,	fully closed position.	organic compounds or heavy metals as
Cadiz model F9489 C,		a result of treatment with wood-
Rodano model F9489 P,		preservatives or coatings.
Atika model F9489 D,		
Zion Keramik model F9489 K, Zion Serpentino model F9489 F,		
Andorra Exclusive model F9489 O and		
Toledo model F9489 I 5kW multifuel stoves manufactured by THORMA Vyroba k.s., Šavol'ská cesta 323/1, 986 01, Fil'akovo- Priemyselný obvod, Slovakia.		
Aquila 450 Contemporary, Corvus 450 Traditional, Corvus 450 Contemporary and Vega 450 Traditional 4.5kW multifuel inset stoves manufactured	Instruction manual dated 28th July 2015, reference: "Aquila 450 / Corvus 450 / Vega 450 Solid Fuel Stoves Manual Version 1.1 Issued 28/07/2015 Inset Versions Supplement".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

(1) Class	(2) Conditions	
of fireplace by F.E. Robinson	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): a result
(Hooton) Limited, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.		of treatment with wood- preservatives or coatings.
Arte 1Vh 66 – A – P3, Arte 1Vh 66 – A1 – P3, Arte 1Vh 66 X – A – P3 and Arte 1Vh 66 X – A1 – P3 6.6kW wood burning inset roomheaters manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, 49324 Melle, Germany.	Instruction manual dated September 2014 reference "Version 09 / 2014".  The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 8mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Arte 2LRh 66 – A – P3 and Arte 2LRh 66 – A1 – P3 12kW wood burning inset roomheaters manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, 49324 Melle, Germany.	Instruction manual dated July 2015 reference "Version 07 / 2015".  The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 14mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ashdale FB2MF 7kW multifuel stove manufactured by ACR Heat Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	The appliance must be fitted with a meenamear stop to	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result

(1) Class of fireplace	(2) Conditions	
бузисрийсе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): of treatment with woodpreservatives or coatings.
Barbas Unilux-6 40 5kW wood-burning Inset appliance manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Instructions for use & Maintenance Manual dated 12 <sup>th</sup> October 2015 reference "Version number: 01-340650".  The appliance must be fitted with an air slider which has a permanent opening of 530mm <sup>2</sup> so as to provide air supply when the air slider is fully closed.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Barbas Unilux-6 52 8kW wood-burning Inset appliance manufactured by Interfocos BV, Hallenstraat 17, NL-5531 AB, BLADEL, Netherlands.	Instructions for use & Maintenance Manual dated 12 <sup>th</sup> October 2015 reference "Version number: 01-340443".  The appliance must be fitted with an air slider which has a permanent opening of 530mm <sup>2</sup> so as to provide air supply when the air slider is fully closed.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Barbas Unilux-6 55 9kW wood-burning Inset appliance manufactured by Interfocos BV, Hallenstraat 17, NL-5531 AB, BLADEL, Netherlands.	Instructions for use & Maintenance Manual dated 12 <sup>th</sup> October 2015 reference "Version number: 01-340859."	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-

(1) Class of fireplace	(2) Conditions	
бузпершсе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): preservatives or coatings.
Barbas Unilux-6 65 8kW wood-burning Inset appliance manufactured by Interfocos BV, Hallenstraat 17, NL-5531 AB, BLADEL, Netherlands.	Instructions for use & Maintenance Manual dated 12 <sup>th</sup> October 2015 reference "Version number: 01-340184".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
		Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Barbas Universal-6 65 9 kW inset roomheater manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Barbas Universal-6 65 installation instructions dated 30 March 2015 reference "01 – 339764", Barbas Universal-6 65 instructions manual dated 30 March 2015 reference "01 – 339760".  The appliance must be fitted with an air slider which has a permanent circular opening of 27mm diameter (570 mm²) so as to provide air supply when the air slider is fully closed.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
	Barbas Universal-6 70 installation instructions dated 30 March 2015 reference "01 – 338117". Barbas Universal-6 70 instructions manual dated 30 March 2015 reference "01 – 338113".  The appliance must be fitted with an air slider which has a permanent circular opening of 27mm diameter (570 mm²) so as to provide air supply when the air slider is fully closed.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Barbas Universal-6 75 10 kW inset roomheater manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Barbas Universal-6 75 installation instructions dated 30 March 2015 reference "01 – 339319". Barbas Universal-6 75 instructions manual dated 30 March 2015 reference "01 – 339315".  The appliance must be fitted with an air slider which has a permanent circular opening of 27mm diameter (570 mm²) so as to provide air supply when the air slider is fully closed.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Barbas Universal-6 80 12 kW inset roomheater manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	Barbas Universal-6 80 installation instructions dated 30 March 2015 reference "01 – 338396". Barbas Universal-6 80 instructions manual dated 30 March 2015 reference "01 – 338392".  The appliance must be fitted with an air slider which has a permanent circular opening of 27 mm diameter (570 mm²) so as to provide air supply when the air slider is fully closed.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
	Barbas Universal-6 85 installation instructions dated 30 March 2015 reference "01 – 339439". Barbas Universal-6	Wood logs. The fuel

(1) Class of fireplace	(2) Conditions	
бузпершсе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
inset roomheater manufactured by Interfocos BV, Hallenstraat 17, NL-5531, AB, BLADEL, Netherlands.	85 instructions manual dated 30 March 2015 reference "01 – 339435".  The appliance must be fitted with an air slider which has a permanent circular opening of 27mm diameter (570 mm²) so as to provide air supply when the air slider is fully closed.	must not contain halogenated organic compounds or heavy metals as a result of treatment with woodpreservatives or coatings.
Bella UK model 14980000, Bella UK without Sideglass model 14980100, Bella High UK model 14981000 and Bella High without Sideglass UK model 14981500 5kW wood burning stoves manufactured by Jydepejsen A/ S, Ahornsvinget 3-7, Nr Felding, DK-7500, Holstebro, Denmark.	Instruction manual dated July 2015, reference "Installation and Operating manual Revision 1, 23-07-2015".  The appliance must be modified to fix the secondary air control to 1300mm² in its minimum position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
BioWIN2 wood pellet boilers models: BWE 102, BWK 102, BWP102, BWE 152, BWK152, BWF 212, BWK 212, BWK 212, BWF 262 and BWP 262 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager- Str. 20, A-5201 Seerkirchen	Operating Manual BioWIN 2 dated July 2015 reference "093406/03". Assembly instructions BioWIN 2 dated July 2015 references "093403/04".	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
bei Salzburg, Austria.		
BLISS Ariel 5S & 5G 5kW Inset multi-fuel stoves manufactured by Tile Tec Fireplaces Limited	Installation and Operating Instructions dated 04/15 reference "BLISS Inserts Issue 01".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds
Private Road 2,  Colwick Industrial Estate,		or heavy metals as a result of treatment with wood-
Colwick, Nottingham		preservatives or coatings.
NG4 2JR.		
BLISS Charon 10S & 10G 10kW Inset multi-fuel Stoves manufactured by Tile Tec Fireplaces Limited	Installation and Operating Instructions dated 04/15 reference "BLISS Inserts Issue 01".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 10% open position.	Wood logs. The fuel must not contain halogenated organic compounds
Private Road 2,		or heavy
Colwick Industrial Estate,		metals as a result of treatment with wood-
Colwick, Nottingham		preservatives or coatings.
NG4 2JR.		
BLISS TFG 5 5kW Freestanding wood burning Stove manufactured by Tile Tec Fireplaces Limited  Private Road 2,	Installation and Operating Instructions dated 04/15 reference "TFG Stoves BLISS Issue 01".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% and Primary air control beyond the 10% open positions.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Colwick Industrial Estate,  Colwick, Nottingham,  NG4 2JR.		of treatment with wood- preservatives or coatings.
BLISS TFG 8 8kW Freestanding wood burning Stove manufactured by Tile Tec Fireplaces Limited Private Road 2, Colwick Industrial Estate, Colwick, Nottingham, NG4 2JR.	Installation and Operating Instructions dated 04/15 reference "TFG Stoves BLISS Issue 01".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 25% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bohemia X40 Cube Panorama 4.5kW multifuel stove manufactured by	Installation and Operating Instructions for Bohemia X Freestanding Multifuel stoves dated June 2015 reference "Pevex1021/AH/ver1".  A permanent stop must be implemented ensuring a minimum opening area of 1cm² for the primary air slider when in the fully closed position and a tertiary air inlet area of 4cm².	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
wide 5.5kW multifuel stove manufactured by Pevex Enterprises Ltd, Unit MP7,	"Pevex1021/AH/ver1".  The appliance must be fitted with a permanent stop that	Wood logs. The fuel must not contain halogenated organic compounds

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Park, Newbourne Road, Nr Woodbridge, IP12 4PR.		or heavy metals as a result of treatment with wood-preservatives or coatings.
Bohemia X60 Cube and Bohemia X60 Cube Panorama 7kW multifuel stoves manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Bohemia X Freestanding Multifuel stoves dated June 2015 reference "Pevex1021/AH/ver1".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Bristol 4.6kW multifuel inset appliance manufactured by Bronpi Calefaccion, Carretera Cordoba-Malaga Km 78.2. Spain.	Bronpi Installation Instructions. Version 3 Issued 15-12-2014.  Bronpi Supplementary Instructions Mod. Bristol. Version 7 Issued 23-01-2015.  Appliances must be fitted with a permanent stop to prevent closure of the air control beyond 25% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bristol-C 4.6kW multi-fuel stove manufactured by Bronpi Calefaccion, Carretera Cordoba- Malaga Km 78.2. Spain.	Bronpi Installation Instructions.  Version 3 Issued 15-12-2014 Bronpi Supplementary Instructions Mod. Bristol-V. Version 7 Issued 23-01-2015.  Appliances must be fitted with a permanent stop to prevent closure of the air control beyond 25% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):  a result
		of treatment with wood- preservatives or coatings.
Bristol-Vision 4.6kW multi-fuel insert manufactured by Bronpi Calefaccion, Carretera Cordoba- Malaga Km 78.2. Spain.	Bronpi Installation Instructions. Version 3 Issued 15-12-2014 Bronpi Supplementary Instructions Mod. Bristol-C. Version 7 Issued 23-01-2015.  Appliances must be fitted with a permanent stop to prevent closure of the air control beyond 25% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Bucklesham 35FS, and Bucklesham 35FS Panorama, 3.8kW multifuel stoves manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Bucklesham 35/40/50/60 FS Multifuel stoves dated June 2015 reference "Pevex1020/AH/ver1".  The appliance must be fitted with a permanent stop that ensures the air control cannot close beyond the 15% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bucklesham 40FS, and Bucklesham 40FS Panorama, 4.5kW multifuel stoves manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr	Installation and Operating Instructions for Bucklesham 35/40/50/60 FS Multifuel stoves dated June 2015 reference "Pevex1020/AH/ver1".  A permanent stop must be implemented ensuring a minimum opening area of 1cm² for the primary air slider when in the fully closed position and a tertiary air inlet area of 4cm².	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

(1) Class of fireplace	(2) Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): with wood-
Woodbridge, IP12 4PR.		preservatives or coatings.
Bucklesham 50FS, and Bucklesham 50FS Panorama, 5kW multifuel stoves manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Bucklesham 35/40/50/60 FS Multifuel stoves dated June 2015 reference "Pevex1020/AH/ver1".  A permanent stop must be implemented ensuring a minimum opening area of 1cm² for the primary air slider when in the fully closed position and a tertiary air inlet area of 4cm².	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Bucklesham 60FS Panorama and Bucklesham 60FS 7kW multifuel stove manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Bucklesham 35/40/50/60 FS Multifuel stoves dated June 2015 reference "Pevex1020/AH/ver1".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Capital Fireplaces Qube 450 multifuel stove manufactured by F.E. Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	Instruction manual dated 28 July 2015 reference "Qube 450/ Vega 450 Qube Solid Fuel Stoves Manual Version 1.1".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-

(1) Class of fireplace	(2) Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): preservatives
Charnwood Bembridge 5kW wood burning stove manufactured by A.J. Wells and Sons Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual references "The Bembridge Operating & Installation Instructions v1 03.015" dated March 2015.  The appliance must be fitted with a mechanical stop to prevent air control opening closure beyond the 58mm open position.	or coatings.  Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Charnwood C-FOUR insert 5kW multifuel inset roomheater manufactured by A.J. Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.	Operating & Installation Instructions manual dated October 2014 reference "REV.C CFOURI 10.14".  Blanking plate (part number 010/TR099) must be in place when burning wood.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
CITIZEN MF 700-60 WHE 1S – DEFRA 14.5kW,  CITIZEN MF 900-45 WHE 1S – DEFRA 12kW,  CITIZEN MF 900-60 WHE 1S – DEFRA 15kW and,  CITIZEN MF 1050-45 WHE 1S	Installation and instructions for use manual dated 29th July 2015 reference "CIT_WHE_EN_02_DEFRA"	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class of fireplace	(2) Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
- DEFRA 13kW wood-burning inset roomheaters manufactured by MetalFire nv. Noorwegenstraat 28, B-9940 Evergem, Belgium.		
Cleanburn Inset 5 CBC 4.7kW wood- burning inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Installation and Operating Instructions dated 30/06/2015 reference "JINCCB04 RevB".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Cleanburn R4 Euro 4.9kW wood-burning stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Installation and Operating Instructions dated 29/01/2015 reference "JINCLE04 RevA" and Smoke Control Area Kit Installation Instructions dated 05/12/11 reference "JINCLR04SCK revB".  Fitted with "smoke control area kit "JCLR0401"".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Cleanburn Skagen 5 HCE85 4.9kW wood-burning stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge,	Installation and operating instructions manual dated 23 <sup>rd</sup> June 2015 reference "JINHCE85 Rev B" and Smoke Control Area Kit Installation Instructions dated 22 <sup>nd</sup> January 2015 reference "JINHCE85SCK revA".  Appliance must be fitted with the manufacturer's smoke control kit reference JHCE8501.	Wood logs. The fuel must not contain halogenated organic compounds or heavy

(1) Class	(2) Conditions	
of fireplace  Camelford,	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): metals as
Cornwall, PL32 9TT.		a result of treatment with wood- preservatives or coatings.
	Instruction manual dated July 2015, reference "811142 BAV GB-8" and Lighting and Installation Instructions dated March 2015 reference "811216 IAV SE-EX Ci6-4".  The fitting of a system to prevent closure of the air control vent beyond the 30% open position must be implemented to be installed in accordance with additional installation instruction ref "811188 Kompletterande IAV Ci5 GB – 4" dated 2014-02-13.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Cosmo Classic UK, Cosmo 1147 UK, Cosmo 1147 Soapstone UK, Cosmo 971 UK, Cosmo 971 Soapstone UK, Cosmo High Soapstone UK, Cosmo 1500 UK and Cosmo 1500 Soapstone UK 6kW stoves manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	User's manual dated June 2011 reference "Cosmo & Midi. User's manual. Jydepejsen A/S – June 2011".  The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 16% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Country 575 and 765 5kW stoves manufactured by Jydepejsen A/S, Ahornsvinget 3-7,	Installation and Operation manual dated March 2015 reference "Installation and Operation Manual Country Revision 1, 25.03.2015".	Wood logs. The fuel must not contain halogenated

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Nr. Felding, DK-7500 Holstebro, Denmark.	The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 35% open position.	organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Cubic Wall UK, Cubic 109 UK, Cubic 166 UK, Cubic 215 UK and Cubic W200 UK 6kW stoves manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	User's manual dated June 2011 reference "Cosmo & Midi. User's manual. Jydepejsen A/S – June 2011".  The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 16% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Dalby Smoke Control and Saltburn Smoke Control 5kW wood-burning stoves manufactured by Town & Country Fires Limited, 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA.	Saltburn Smoke Control / Dalby Smoke Control and wood burning stove installation and user instructions dated 6 July 2015 reference "Saltburn/Dalby Smoke Control Issue 2".  The appliances must be fitted with a mechanical stop to prevent closure of the air control slider beyond the 30mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Di Lusso R4 Euro 4.9kW wood-burning stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge,	reference "JINDLE04 RevA" and Smoke Control Area	Wood logs. The fuel must not contain halogenated organic compounds

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Camelford, Cornwall, PL32 9TT.		or heavy metals as a result of treatment with wood- preservatives or coatings.
Ecosy+ Ottawa 5 multi-fuel stove manufactured by Stove World UK Limited, Unit 24 Folly Farm, Ramsdell, Tadley, RG26 5RJ.	Installation and Operating Instructions dated 04/06/15 reference "Ottawa 5kw Operating Instructions Version 1".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 31mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ecosy+ Ottawa 12 multi-fuel stove manufactured by Stove World UK Limited, Unit 24 Folly Farm, Ramsdell, Tadley, RG26 5RJ.	Instruction manual dated 04/06/15 reference "Ottawa 12kw Operating Instructions Version 1".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 31mm open position when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Effecta Komplett III 20kW and Effecta Komplett III light 20kW pellet boilers manufactured by Effecta Energy Solutions AB, Västra Rågdalsvägen 21,	The EFFECTA KOMPLETT III – Installing, - Maintenance, - Service, - Assembly Instruction dated 29 <sup>th</sup> June 2015 reference "Rev. E.A. Ver 02".	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as

(1) Class	(2) Conditions	
of fireplace	(2) Contamons	
424 00 W	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
434 99 Kungsbacka, Sweden.		a result of treatment with wood- preservatives or coatings.
ETA HACK VR BG 2 333 and ETA HACK VR BG 2 350 moving grate boiler size 2 manufactured by ETA Heiztechnik GmbH, Gewerbepark 1, 4716, Austria.	Instruction manual dated 12 January 2015 reference "EN0000000039 V.010 X.30.0 3500".	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Evolution 5 models M-EVO5/MF, EVO5/MF, EVO5/MF/DLX, M-EVO5/MF/LOG & model M-EVO5/MF/LOG/DLX 5kW multi-fuel stoves manufactured by Broseley Fires Limited, First Floor, Unit B Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, SY1 3GA.	Installation & Operating Instructions manual dated 21 <sup>st</sup> July 2015 reference "Evolution 5MF Issue 1".  The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 10% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Falun Model F9478, Falun II model F9480 I, Alvesta model F9478 I,	Installation and Operation Manual dated 27 <sup>th</sup> July 2015 reference "FALUN – Version A".  The appliance must be fitted with a modified air regulator which has a permanent opening of 388mm <sup>2</sup> when in the fully closed position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Alvesta II model F9478 T, Landshut model F9478 L, Landshut II model F9478 N, Kiruna II model F9478 2, Kiruna II box model F9478 4, Atomic model F9478 G, Ribe model F9480 E, Cremona model F9480,		metals as a result of treatment with wood-preservatives or coatings.
Wikantica model 9480 T and Wiesbaden model F9480 2		
5kW multifuel stoves manufactured by THORMA Vyroba k.s., Šavol'ská cesta 323/1, 986 01, Fil'akovo- Priemyselný obvod, Slovakia.		
Farringdon 8kW freestanding wood burning stove manufactured by Arada Limited, The Fireworks, Weycroft Avenue, Axminster, Devon, EX13 5HU.	Operating & Installation manual dated 01/09/2015 reference "AFS P0134 Rev 04".  The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 29mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	(=)	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Fat Penguin, Hungry Penguin and High and Mighty Penguin 5kW multifuel stoves manufactured by Chilli Penguin Stoves Limited, Castell Bach, Mynydd Nefyn, Pwllheli, LL53 6TL.	Installation and Operating Instructions manual dated June 2015 reference "CPS 9768".  The appliance must be fitted with a mechanical stop to prevent closure of the secondary air controller beyond 17mm from the closed position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
FDC Ariel 5S & 5G 5kW Inset multi-fuel Stoves manufactured by FDC (UK) Ltd Unit C4 Dinton Business Park, Catherine Ford Road, Dinton, Salisbury, Wiltshire, SP3 5HZ.	Installation and Operating Instructions dated 04/15 reference "FDC Inserts Issue 01".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
FDC Charon 10S & 10G 10kW Inset multi-fuel Stoves manufactured by FDC (UK) Ltd Unit C4 Dinton Business Park, Catherine Ford Road, Dinton, Salisbury, Wiltshire, SP3 5HZ.	Installation and Operating Instructions dated 04/15 reference "FDC Inserts Issue 01".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 10% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
FDC TFG 5 5kW Freestanding wood	Installation and Operating Instructions dated 04/15 reference "TFG Stoves FDC Issue 01".	Wood logs. The fuel

(1) Class	(2) Conditions	
of fireplace	, ,	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
burning Stove manufactured by FDC (UK) Ltd  Unit C4 Dinton Business Park, Catherine Ford Road, Dinton, Salisbury, Wiltshire, SP3 5HZ.	Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% and Primary air control beyond the 10% open positions.	must not contain halogenated organic compounds or heavy metals as a result of treatment with woodpreservatives or coatings.
FDC TFG 8 8kW Freestanding wood burning Stove manufactured by FDC (UK) Ltd  Unit C4 Dinton Business Park, Catherine Ford Road, Dinton, Salisbury, Wiltshire, SP3 5HZ.	Installation and Operating Instructions dated 04/15 reference "TFG Stoves FDC Issue 01".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 25% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Fireglow ST3, Saltfire ST3 and Ultimo ST3 7.3kW wood-burning stoves manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG.	Saltfire ST3, Fireglow ST3 and Ultimo ST3 installation and operation instructions dated 7th July 2015 reference "ST3/Version 1.0".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Fireglow ST4, Saltfire ST4 and Ultimo ST4 7.5kW multifuel stoves	Saltfire ST3, Fireglow ST3 and Ultimo ST3 installation and operation instructions dated 7th July 2015 reference "ST4/Version 1.0".	Wood logs. The fuel must not contain

(1) Class	(2) Conditions	<u> </u>
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG.		halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Grant Vectra 4-16 16kW condensing wood pellet boiler manufactured by Grant (UK) Limited, Hopton House, Hopton Industrial Estate, Devizes, Wiltshire, SN10 2EU.	Installation & Servicing Instructions manual dated July 2015 reference "Part No. DOC.47 Rev.06 13/07/15".	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Greenflame Eco 10kW Model Number FG3730, FG3731, FG3790, FG3791.  Greenflame Eco 15kW Model Number FG3732, FG3733, FG3792, FG 3793.  Greenflame Eco 25kW Model Number FG3734, FG3735, FG3794, FG3795.	Greenflame Eco Wood Pellet Boiler 10-60 kW Installation, Operation and Servicing Instructions manual dated April 2015 reference "400012".	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Greenflame Eco 40kw Model		

(1) Class of fireplace	(2) Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Number FG3736, FG3737, FG3796, FG3797.		
Greenflame Eco 60kW Model Number FG3738, FG3739, FG3743, FG3798, FG3799 manufactured by T.R. Engineering Ltd, Unit 7 Newtown Chambers Way, Thornecliffe, Chapeltown, Sheffield, S35 2PH.		
Hereford 5 and 7 multifuel stoves manufactured by Broseley Fires Limited, First Floor, Unit B Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, SY1 3GA.	Installation & Operating Instructions manual dated 8th July 2015 reference "Mar 14/GB Issue 5".  The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slide beyond the 10mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Herz Firematic 349 (349kW), 401 (401kW), and 499 (499kW) boilers manufactured by Herz Energietechnik GmbH, Herstraße 1, 7423 Pinkafeld, Austria.	Operating Instructions dated December 2014 reference "Betriebsanleitung_Firematic_20_499_Touch_Englisch_V1 and supplementary document dated 28 <sup>th</sup> April 2015 reference "CleanAirAct1993_20150507HERZ-ET".	Wood chips And wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-

(1) Class of fireplace	(2) Conditions	
бузпершее	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): preservatives
Heta Inspire 55 and 55H 6.3kW stoves manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig, Denmark.	Operating Instructions dated July 2015 reference "Pevex1020/AH/ver2."  Fitted with a mechanical stop to prevent air control closure beyond the 41% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hörby Model F9473 N,	Installation and Operation Manual dated 27th July 2015 reference "HORBY – Version A".	Wood logs. The fuel
Borgholm II model F9473 E, Torino model F9473 I,	The appliance must be fitted with a mechanical stop to prevent closure of the air control lever beyond the 3mm open position.	must not contain halogenated organic compounds or heavy
Loholm model F9473 L,		metals as a result of treatment with wood-
Ulsborg model F9473 2,		preservatives or coatings.
Augsburg model F9473 K,		
Nancy model F9472 O,		
Passau model F9472 R,		
Basel II model F9472 H,		

(1) Class of fireplace	(2) Conditions	
буунериасе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Skal II model F9472 P,		
Nancy II model F9472 Y,		
Domino IIFS model F9472 V and Colmar model F9472 X 5kW multifuel stoves manufactured by THORMA Vyroba k.s., Šavol'ská cesta 323/1, 986 01, Fil'akovo- Priemyselný obvod, Slovakia.		
Hunter Herald Inset 5 CBC 4.7kW wood-burning inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Installation and Operating Instructions dated 30/06/2015 reference "JINHCB04 RevB".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Hwam 2610, 2620, 2630 and 2640 3.5kW wood- burning stoves manufactured by HWAM Heat Design AS, Nydamsvej 53, 8362 Hørning, Denmark.	Operating and Maintenance Instructions dated July 2015 reference "IN1272 Ed.B".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-

(1) Class of fireplace	(2) Conditions	
бузичериисе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): preservatives
Hwam 3110, 3120, 3410, 3420, 3440, 3520 and 3530 4.5kW wood- burning stoves manufactured by HWAM Heat Design AS, Nydamsvej 53, 8362 Hørning, Denmark.	Operating and Maintenance Instructions dated January 2015 reference "IN1211 Ed B".	wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Hwam 3610, 3620, 3630, 3640, 3650, 3660 6kW woodburning stoves manufactured by HWAM Heat Design AS, Nydamsvej 53, 8362 Hørning, Denmark.	Ed A".  Fitted with a mechanical stop to prevent air control closure	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Hwam 30/55 7kW inset wood-burning stove manufactured by HWAM Heat Design AS, Nydamsvej 53, 8362 Hørning, Denmark.	1 2	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
I Series 600 SLF L/M 5kW freestanding wood burning stove manufactured by Arada Limited, The Fireworks, Weycroft Avenue, Axminster, Devon, EX13 5HU.	Operating & Installation manual dated 01/09/2015 reference "AFS P0133 Rev. H".  The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 20mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Keddy K700 5.9kW wood-burning stove manufactured by Keddy AB, PO Box 542, 441 15 Alingsas, Sweden.	K700 Installation Instructions Care and Firing Instructions dated 1st May 2015 reference "Rev 1.".  Fitted with a mechanical stop to prevent air control closure beyond the 30% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
wood-burning stove manufactured by	K800 Installation Instructions Care and Firing Instructions dated 1st September 2013 reference "Rev 1.".  Fitted with a mechanical stop to prevent air control closure beyond the 25% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
	K1100 Installation Instructions Care and Firing Instructions dated 1st September 2014 reference "Rev 1.".	Wood logs. The fuel

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
manufactured by Keddy AB, PO Box 542, 441 15 Alingsas, Sweden.	Fitted with a mechanical stop to prevent air control closure beyond the 30% open position.	must not contain halogenated organic compounds or heavy metals as a result of treatment with woodpreservatives or coatings.
Keddy SK1000 5.9kW wood-burning inset roomheater manufactured by Keddy AB, PO Box 542, 441 15 Alingsas, Sweden.	instructions Model SK1000 dated 1st September 2013	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
KWB Multifire MF2 D/ZI 20 biomass boiler, KWB Multifire MF2 D/ZI 30 biomass boiler, KWB Multifire MF2 D/ZI 40 biomass boiler, KWB Multifire MF2 D/ZI 45 biomass boiler, KWB Multifire MF2 D/ZI 50 biomass boiler, KWB Multifire MF2 D/ZI 60 biomass boiler, KWB Multifire MF2 D/ZI 65 biomass boiler, KWB	Operation Manual KWB Multifire MF2 D/ZI dated July 2015 references "Index 3 EN".	Wood chip and wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Multifire MF2 D/ZI 70 biomass boiler, KWB Multifire MF2 D/ZI 80 biomass boiler, KWB Multifire MF2 D/ZI 99 biomass boiler, KWB Multifire MF2 D/ZI 100 biomass boiler, KWB Multifire MF2 D/ZI 101 biomass boiler, KWB Multifire MF2 D/ZI 101 biomass boiler, KWB Multifire MF2 D/ZI 108 biomass boiler, and KWB Multifire MF2 D/ZI 120 manufactured by Kraft und Wärme aus Biomasse GmbH, Industriestraße 235, A-8321 St Margarethen Straße, Austria.		
KWB Pelletfire Plus MF2 S/GS 45 pellet boiler, KWB Pelletfire Plus MF2 S/GS 50 pellet boiler, KWB Pelletfire Plus MF2 S/GS 55 pellet boiler, KWB Pelletfire Plus MF2 S/GS 65 pellet boiler, KWB Pelletfire Plus MF2 S/GS 70, KWB Pelletfire Plus MF2 S/GS 75 pellet boiler, KWB Pelletfire Plus MF2 S/GS 75 pellet boiler, KWB Pelletfire Plus MF2 S/GS 75 pellet boiler, KWB Pelletfire Plus MF2 S/GS	Operation Manual KWB Pelletfire Plus MF2 S/GS dated July 2015 references "Index 3 EN".	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class of fireplace	(2) Conditions	
бузпершсе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
KWB Pelletfire Plus MF2 S/GS 99 pellet boiler, KWB Pelletfire Plus MF2 S/GS 100 pellet boiler, KWB Pelletfire Plus MF2 S/GS 101 pellet boiler, KWB Pelletfire Plus MF2 S/GS 108 pellet boiler, KWB Pelletfire Plus MF2 S/GS 108 pellet boiler, KWB Pelletfire Plus MF2 S/GS 115 pellet boiler, KWB Pelletfire Plus MF2 S/GS 115 pellet boiler, KWB Pelletfire Plus MF2 S/GS 135 manufactured by Kraft und Wärme aus Biomasse GmbH, Industriestraße 235, A-8321 St Margarethen Straße, Austria.		
LogWIN Klassik wood log classification boilers models: LWK 180, LWK 250 and LWK 300 manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str. 20, A-5201 Seerkirchen bei Salzburg, Austria.	Operating Manual LogWIN Klassik dated July 2015 reference "093394/02". Assembly instructions LogWIN Klassik dated July 2015 references "093391/03".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
LogWIN Premium wood log gasification boilers models: LWP 180, LWP 250, LWP 300,	Operating Manual LogWIN Premium dated July 2015 reference "092412/05". Assembly instructions LogWIN Premium dated July 2015 references "092413/05".	Wood logs. The fuel must not contain halogenated

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
LWP 360 and LWP 500 manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seerkirchen bei Salzburg, Austria.		organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Lotus Liva 5, Liva 5S, Liva 6G, Liva 6S and Liva 6G 5kW wood-burning stoves manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov, Denmark.	Instruction manual dated July 2015 reference "Mounting and User Instructions Lotus-Liva (Lotus Liva 5, Liva 6) version 3, 20/7-2015".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Lotus Mira 1 and Mira 2 5kW wood- burning stoves manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov, Denmark.	Instruction manual dated July 2015 reference "Mounting and User Instructions Lotus-Mira Series Stoves (Lotus Mira 1/2, Mira 3/4) version 4, 20/7-2015".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Lundy, Skye and Ramsey 5kW pellet stoves manufactured by Island Pellet Stoves Ltd, Tugbury House, Unit 26 Main Avenue, Treforest	Owners' manual for 5kW pellet stove models: - Lundy, Skye and Ramsey dated 16th July 2015 reference "5kW Stove".	Wood pellets. The fuel must not contain halogenated organic compounds

(1) Class	(2) Conditions	
of fireplace  Industrial Estate,	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Pontypridd, CF37 5UR.		metals as a result of treatment with wood- preservatives or coatings.
Lundy, Skye and Ramsey 8kW pellet boiler stoves manufactured by Island Pellet Stoves Ltd, Tugbury House, Unit 26 Main Avenue, Treforest Industrial Estate, Pontypridd, CF37 5UR.	Owners' manual for 8kW pellet boiler stove models: -Lundy, Skye and Ramsey dated 16th July 2015 reference "8kW boiler stove".	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Meg 4.5 Pod and Meg Sirius 450 Qube 4.5kW multifuel stoves manufactured by F.E. Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	Instruction manual dated 10 July 2015 reference "Meg Solid Fuel Stoves Manual Version 1.4. Issued 15/07/2015".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Mido UK, Mido Soapstone UK 6kW stoves manufactured by Jydepejsen A/ S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	The appliance must be fitted with a mechanical stop to	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

(1) Class of fireplace	(2) Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): a result of treatment with wood- preservatives or coatings.
Mi Stoves Taymin 5 CB 4.9kW multifuel stove manufactured by Capital Fireplaces Ltd, Units 12-17, Henlow Trading Estate, Henlow Camp, SG16 6DS.	Installation & Operating Instructions dated 26 <sup>th</sup> June 2015 reference "15JUN09/TA5/V1.2".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Mi Stoves Taymin 8 CB 8.9kW multifuel stove manufactured by Capital Fireplaces Ltd, Units 12-17, Henlow Trading Estate, Henlow Camp, SG16 6DS.	Installation & Operating Instructions dated 26 <sup>th</sup> June 2015 reference "15JUN10/TA8/V1.4".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Neo models 1C, 1P, 1W, 3C, 3P and 3W 5kW multifuel stoves manufactured by ACR Heat Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.		Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment

(1) Class of fireplace	(2) Conditions	
бузисрійсе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): with wood-preservatives or coatings.
Nero D IHS, Nero M IHS, Vecto D IHS, Vecto M IHS and Orbit 6kW IHS free standing wood-burning stoves manufactured by Dan Skan GmbH, Burgwedeler Str. 7-8, D-30657 Hannover, Germany.	Instruction manual dated November 2014 reference "DSB2-Defra / UK-NI-ROI / V3.01.15."  A modification to prevent closure of the air flow control valve below position 2 must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Newbourne 35FS, and Newbourne 35FS Panorama, 3.8kW multifuel stoves manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Newbourne 35/40/50/60 FS Multifuel stoves dated June 2015 reference "Pevex1022/AH/ver1".  The appliance must be fitted with a permanent stop that ensures the air control cannot close beyond the 15% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Newbourne 40FS and Newbourne 40FS Panorama 4.5kW multifuel stoves manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Newbourne 35/40/50/60 FS Multifuel stoves dated June 2015 reference "Pevex 1022/AH/ver1".  A permanent stop must be implemented ensuring a minimum opening area of 1cm² for the primary air slider when in the fully closed position and a tertiary air inlet area of 4cm².	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): preservatives or coatings.
Newbourne 40i 4.5kW multifuel inset roomheater manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Newbourne 40 inset multifuel stoves dated June 2015 reference "Pevex 1033/AH/ver1:June2015".  The appliance must be fitted with permanent stops that ensure the primary and tertiary air controls do not close beyond 0.5cm open and 2cm open positions respectively.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Newbourne 50FS and Newbourne 50FS Panorama 5kW multifuel stoves manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Newbourne 35/40/50/60 FS Multifuel stoves dated June 2015 reference "Pevex1022/AH/ver1".  A permanent stop must be implemented ensuring a minimum opening area of 1cm² for the primary air slider when in the fully closed position and a tertiary air inlet area of 4cm².	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Newbourne 60FS Panorama and Newbourne 60FS 7kW multifuel stove manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR.	Installation and Operating Instructions for Newbourne 35/40/50/60 FS Multifuel stoves dated June 2015 reference "Pevex1022/AH/ver1".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	(2) Contamons	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Oakdale FB1MF 5kW multifuel stove manufactured by ACR Heat Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	Technical manual dated 17th February 2015 reference "Document FB1MF 0101 Version 2".  The appliance must be fitted with a mechanical stop to prevent closure of the secondary air slider beyond the 25mm open position and the tertiary air control will be fixed in the fully open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
	Installation and Operation manual dated June 2015 reference "Omega, Omega High, .User manual. Revision 1, 25.03.2015".  The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 27% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Orion UK and Orion Soapstone UK 7kW stoves manufactured by Jydepejsen A/ S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	User's manual dated March 2015 reference "Sirius & Orion & Troja. User manual. Revision 1, 25.03.2015".  The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 27% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Oxford 4.6kW multifuel stove manufactured by Bronpi Calefaccion, Carretera Cordoba-Malaga Km 78.2. Spain.	Bronpi Installation Instructions. Version 3 Issued 15-12-2014 Bronpi Supplementary Instructions Mod. Oxford Version 7 Issued 23-01-2015.  Appliances must be fitted with a permanent stop to prevent closure of the air control beyond 25% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Parkray Caprice 4 Euro 4.9kW wood-burning stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Installation and Operating Instructions dated 29/01/2015 reference "JINCAE04 RevA" and Smoke Control Area Kit Installation Instructions dated 05/12/11 reference "JINCAP04SCK revB".  Fitted with "smoke control area kit "JCAP0401"".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Parkray Consort Inset 5 CBC 4.7kW wood-burning inset stove manufactured by Hunter Stoves Ltd, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Installation and Operating Instructions dated 30/06/2015 reference "JINPCB04 RevB".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Passat Energy HO180 199kW	User's guide dated 11th May 2015 reference "HO User Guide C004_EN Revision date: 14/07/2015". "HO	Wood chip and wood

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
boiler manufactured by Passat Energy A/ S, Vestergade 36, Ørum, 8830 Tjele, Denmark.	Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015.	pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with woodpreservatives or coatings.
Passat Energy HO250 249kW boiler manufactured by Passat Energy A/ S, Vestergade 36, Ørum, 8830 Tjele, Denmark.	Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
	dated 18th February 2013 Version C002_EN Revision date	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Passat Energy HO420 501kW boiler manufactured	,	Wood pellets. The fuel must

(1) Class of fireplace	(2) Conditions	
s, y m sprints	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
by Passat Energy A/S, Vestergade 36, Ørum, 8830 Tjele, Denmark.	dated 18th February 2013 Version C002_EN Revision date 14th July 2015."	not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Passat Energy HO510 595kW boiler manufactured by Passat Energy A/ S, Vestergade 36, Ørum, 8830 Tjele, Denmark.	Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
HO680 790kW boiler manufactured	Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
HO850 990kW boiler manufactured	User's guide dated 11th May 2015 reference "HO User Guide C004_EN Revision date: 14/07/2015". "HO Maintenance Description Automatic Solid Fuel Boiler dated 18th February 2013 Version C002_EN Revision date 14th July 2015."	Wood pellets. The fuel must not contain halogenated

(1) Class	(2) Conditions	
of fireplace  Ørum, 8830 Tjele, Denmark.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): organic compounds
Definition.		or heavy metals as a result of treatment with wood- preservatives or coatings.
Pellux 100/20 20kW wood pellet boiler manufactured by NIBE Energy System Ltd, Unit 3c, Broom Bank Business Park, Bridge Way, Chesterfield, S41 9QG.	Installation & Operating Manual dated '2015-02-24'. Reference '24148'.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with woodpreservatives or coatings.
Pellux 100/30 30kW wood pellet boiler manufactured by NIBE Energy System Ltd, Unit 3c, Broom Bank Business Park, Bridge Way, Chesterfield, S41 9QG.	Installation & Operating Manual dated '2015-02-24'. Reference '24148'.	Wood pellets. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Percy Doughty Vega 450 Qube 4.5kW multifuel stove manufactured by F.E. Robinson (Hooton) Ltd, Station Works,	Instruction manual dated 28 July 2015 reference "Qube 450/Vega 450 Qube Solid Fuel Stoves Manual Version 1.1. Issued 28/07/2015".	Wood logs. The fuel must not contain halogenated organic compounds

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Hooton Road, Hooton, South Wirral, CH66 7NF.		or heavy metals as a result of treatment with wood- preservatives or coatings.
Rais Q-Be 5.9kW wood-burning stove manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction for installation use and maintenance Rais Q-Be dated April 2015 reference "Revision 1".  The appliances must be modified to provide a minimum open area of 554mm² in the secondary air control and 143mm² in the tertiary air control.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rais Visio 2 wood-burning stove and Rais Visio 3 7kW wood-burning stoves manufactured by Rais A/ S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction for installation use and maintenance Visio 2 & Visio 3 dated June 2015 reference "Rev 2a".  The appliances must be modified to provide a minimum open area of 300mm² in the secondary air control and 93mm² in the tertiary air control.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Rais Viva 4.6 kW wood-burning stoves models 98, 98G, 120, 120G, 98 Classic, 98G Classic, 120 Classic and 120G Classic.	Instruction for installation use and maintenance Rais Rina, Rais Viva & Rais Juno including Classic Models dated June 2015 reference "Issue 7a".  The appliances must be fitted with a mechanical stop to prevent closure of the air damper beyond the 8.5mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

(1) Class of fireplace	(2) Conditions	
ој јигершсе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Rais Rina 4.6 kW wood-burning stove.  Rais Rina 4.6 kW wood-burning stoves models 90, 90 Classic, SST, SST Classic.  Rais Juno 4.6 kW wood-burning stove.  Rais Juno 4.6 kW wood-burning stove.  Rais Juno 4.6 kW wood-burning stoves models G, 120 Classic, G 120 Classic, G 1560 Classic, G 1560 Classic, G 1560 Classic, G 1560 Classic, G 1930 Classic manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.		a result of treatment with wood-preservatives or coatings.
Rowandale FB3MF 5kW multifuel stove manufactured by ACR Heat Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	Technical manual dated 17 <sup>th</sup> February 2015 reference "Document FB3MF 0101 Version 2".  The appliance must be fitted with a mechanical stop to prevent secondary air slider closure beyond the 25mm open position, and the tertiary air control will be fixed in the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
S5i 5kW multifuel inset stove	Operating and Installation Instructions manual dated 17 July 2015 reference "ST Version 1.0".	Wood logs. The fuel must not contain

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
S5f 5kW multifuel stove		halogenated organic
S51 5kW multifuel stove		compounds or heavy metals as
G5i 5kW multifuel inset stove		a result of treatment with wood-
G5f 5kW multifuel stove		preservatives or coatings.
G51 5kW multifuel stove		
S9i 9kW multifuel inset stove		
S9f 9kW multifuel stove		
S91 9kW multifuel stove		
G9i 9kW multifuel inset stove		
G9f 9kW multifuel stove		
G9l 9kW multifuel stove manufactured by Stovey Limited, Site 1, Cotwall Lane, High Ercall, Telford, Shropshire, TF6 6JD.		
Serenity 45, 5.5kW multifuel inset roomheater manufactured by Pevex Enterprises Ltd, Unit MP7, Kirrawah Business Park, Newbourne	Installation and Operating Instructions for Serenity 45 inset dated June 2015 reference "Pevex1030/AH/ver1".  The appliance must be fitted with a permanent stop that ensures the air control cannot close beyond 19mm open (position 2).	Wood logs. The fuel must not contain halogenated organic compounds or heavy

(1) Class	(2) Conditions	
of fireplace  Road, Nr	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): metals as
Woodbridge, IP12 4PR.		a result of treatment with wood-preservatives or coatings.
Sherborne SE NS-3C, Chesham SE NS-3B, Burford SE NS-3A 4.9kW multi-fuel stoves manufactured by Newman Fireplaces Ltd, Units 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.	Installation and user instruction manual dated 4 <sup>th</sup> June 2014, reference "NS-3A – NS-3B – NS-3C".  The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Sigma UK 7kW inset roomheater manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	User's manual dated March 2015 reference "Sigma & Sigma Titan. User's manual. Revision 1, 25.03.2015".  The appliance must be fitted with a mechanical stop to prevent closure of the air control valve beyond the 28% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Sirius Imperial, Principal, Qadrical & Essence 4.9kW multifuel stoves manufactured by Capital Fireplaces Ltd, Units 12-17, Henlow Trading Estate, Henlow Camp, SG16 6DS.	Installation & Operating instructions dated 26 <sup>th</sup> June 2015 reference "15JUN08/EQIP/V1.3".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result

(1) Class of fireplace	(2) Conditions	
буулергисс	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): of treatment with wood- preservatives or coatings.
Spartherm Passo S-P3, Spartherm Passo M-P3 and Spartherm Passo L-P3 10kW wood-burning stoves manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, Germany.	Installation and Operating Instructions for Stoves Selection manual dated July 2015 reference "Version 07/2015".  A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 3mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Stovo S-plus – P3 and Stovo L-plus – P3 4.7kW wood burning stoves manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, 49324 Melle, Germany.	Installation and Operating instructions for Stoves Selection manual dated July 2015 reference "Version 07/2015".  The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 5mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
The Stone Bake Oven Company Mezzo 76 Go and Mezzo 76 Kit wood- burning pizza ovens manufactured by Gozney Ltd, Units 18 & 19, Radar Way, Christchurch Business Park, The Runway,	Oven Assembly and Operation Manual dated May 2015 reference "Mezzo_Oven_Manual/ Version 1.1".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised
Christchurch, BH23 4JE.		fuels): preservatives or coatings.
The Stone Bake Oven Company Vento 100 wood- burning pizza ovens manufactured by Gozney Ltd, Units 18 & 19, Radar Way, Christchurch Business Park, The Runway, Christchurch, BH23 4JE.	Vento 100 Oven Assembly and Operation Manual dated May 2015 reference "Vento_Oven_Manual/ Version 1.1".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
The Stone Bake Oven Company Gusto 120 wood- burning pizza ovens manufactured by Gozney Ltd, Units 18 & 19, Radar Way, Christchurch Business Park, The Runway, Christchurch, BH23 4JE.	Gusto 120 Oven Assembly and Operation Manual dated May 2015 reference "Gusto_Oven_Manual/Version 1.1".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Stûv Micromega 11kW wood-burning stove manufactured by Stûv SA Rue Jules Borbouse 4, 5170 Bois-de-Villers, Belgium.	Directions for use Stûv µM manual dated September 2015 reference "SN 122141".  Fitted with a mechanical stop to prevent air control closure beyond the 28% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Tile Tec Fireplaces Bliss 5 CB 4.9kW multifuel stove manufactured by Capital Fireplaces Ltd, Units 12-17, Henlow Trading Estate, Henlow Camp, SG16 6DS.	Installation & Operating Instructions dated 26 <sup>th</sup> June 2015 reference "15JUN09/BL5/V1.2".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Tile Tec Fireplaces Bliss 8 CB 8.9kW multifuel stove manufactured by Capital Fireplaces Ltd, Units 12-17, Henlow Trading Estate, Henlow Camp, SG16 6DS.	Installation & Operating Instructions dated 26 <sup>th</sup> June 2015 reference "15JUN09/BL8/V1.4".  Fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Triton 450 Glass and Vega 450 4.5kW multifuel stoves manufactured by F.E. Robinson (Hooton) Limited, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	Instruction manual dated 28th July 2015, reference: "Triton 450 / Vega 450 / Volan 750 / Vega 750 Solid Fuel Stoves Manual Version 1.1 Issued 28/07/2015".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
1 3	User's manual dated March 2015 reference "Sirius & Orion & Troja. User manual. Revision 1, 25.03.2015".	Wood logs. The fuel

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Troja 46 UK 7kW stoves manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	**	must not contain halogenated organic compounds or heavy metals as a result of treatment with woodpreservatives or coatings.
Tucana 600, Vega 600 6kW multifuel inset stoves manufactured by F.E. Robinson (Hooton) Limited, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	1.1 Issued 28/07/2015".  The appliance must be fitted with a mechanical stop to	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
	Users' manual dated January 2015 reference "Users manual Compact Stoker Cpi12 Version 3.1 – Jan 2015".	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Twin Heat CS120i, CS150i and CS250i boilers manufactured	Stoker Plants CS120i, CS150i, CS200i, CS250i Version 7.1	Wood pellets or wood chips. The

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
by Twin Heat A/S, Nørrevangen 7, DK-9631, Gedsted, Denmark.		fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Twin Heat CS200i boiler manufactured by Twin Heat A/S, Nørrevangen 7, DK-9631, Gedsted, Denmark.	Users manual dated January 2015 reference "Users manual Stoker Plants CS120i, CS150i, CS200i, CS250i Version 7.1 – Jan 2015".	Wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Twin Heat M20i, M40i and M80i boilers manufactured by Twin Heat A/S, Nørrevangen 7, DK-9631, Gedsted, Denmark.	Users manual dated January 2015 reference "Users manual Stoker Plants M20i, M40i, M80i Version 8.1 – Jan 2015".	Wood pellets or wood chips. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
Twin Heat MCS20i, MCS40i and MCS80i boilers	Users' manual dated January 2015 reference "Users' manual Stoker Plants MCS20i, MCS40i, MCS80i Version 2.1 – Jan 2015".	Wood pellets or wood chips. The

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
manufactured by Twin Heat A/S, Nørrevangen 7, DK-9631, Gedsted, Denmark.		fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
ULTIME C MF 600-75 WHE 1S – DEFRA 19.4kW wood-burning inset appliance manufactured by MetalFire nv, Noorwegenstraat 28, B-9940, Evergem, Belgium.	Instruction manual dated May 2015 reference "Instructions for use Ultime C range – Smoke Control Areas (UK) V1 – DEFRA/ May 2015".  The appliances must be fitted with a mechanical stop to the air control to prevent closure beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
800-50 WHE 1S	Instruction manual dated May 2015 reference "Instructions for use Ultime C range - Smoke Control Areas (UK) V1 – DEFRA/ May 2015".  The appliances must be fitted with a mechanical stop to the air control to prevent closure beyond the 11mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ULTIME C MF 800-75 WHE 1S - DEFRA 23.4kW wood-burning inset	Instruction manual dated May 2015 reference "Instructions for use Ultime C range – Smoke Control Areas (UK) V1 – DEFRA/May 2015".	Wood logs. The fuel must not contain

(1) Class	(2) Conditions	
of fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
appliance manufactured by MetalFire nv, Noorwegenstraat 28, B-9940, Evergem, Belgium.	The appliances must be fitted with a mechanical stop to the air control to prevent closure beyond the 11mm open position.	halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ULTIME C MF 1050-50 WHE 1S – DEFRA (21.6kW) and ULTIME C 1300-50 WHE 1S – DEFRA (27kW) wood-burning inset appliances manufactured by MetalFire nv, Noorwegenstraat 28, B-9940, Evergem, Belgium.	Instruction manual dated May 2015 reference "Instructions for use Ultime C range – Smoke Control Areas (UK) V1 – DEFRA/ May 2015".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
ULTIME D MF 600-50 WHE 1S – DEFRA 13.8kW inset roomheater manufactured by MetalFire nv, Noorwegenstraat 28, B-9940 Evergem, Belgium.	Instructions for use Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015" and Installation Instructions Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015".  The appliance must be fitted with a permanent stop to prevent closure of the air control lever beyond the 7mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
ULTIME D MF 600-75 WHE 1S – DEFRA 18.8kW inset roomheater manufactured by MetalFire nv,	Instructions for use Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015" and Installation Instructions Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015".	Wood logs. The fuel must not contain halogenated organic

(1) Class of fireplace	(2) Conditions	
бузиершее	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Noorwegenstraat 28, B-9940 Evergem, Belgium.	The appliance must be fitted with a permanent stop to prevent closure of the air control lever beyond the 15mm open position.	compounds or heavy metals as a result of treatment with wood- preservatives or coatings.
ULTIME D MF 1050-50 WHE 1S – DEFRA 19.4kW inset roomheater manufactured by MetalFire nv, Noorwegenstraat 28, B-9940 Evergem, Belgium.	Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015" and Installation Instructions Ultime D range –	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ULTIME D inset roomheaters models:  MF 800-50 WHE 1S – DEFRA 16.6kW,  MF 800-75 WHE 1S – DEFRA 21.2kW,  MF 1050-75 WHE 1S – DEFRA 23.5kW manufactured by MetalFire nv, Noorwegenstraat 28, B-9940 Evergem, Belgium.	Instructions for use Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015" and Installation Instructions Ultime D range – Smoke Control Areas (UK) dated May 2015 reference "V1 – DEFRA/ May 2015".  The appliance must be fitted with a permanent stop to prevent closure of the air control lever beyond the 11mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Varia AS 11kW wood-burning inset appliances models:  Varia AS-A-P3,	Instruction manual dated September 2015 reference "Instruction manual Fireplace Inserts version 09/2014".	Wood logs. The fuel must not contain halogenated

(1) Class (2) Conditions of fireplace		
буунершее	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Varia ASh-A-P3, Varia AS X-A-P3, Varia ASh X-A-P3, Varia AS-A1-P3, Varia ASh-A1-P3, Varia AS X-A1-P3 and Varia ASh X-A1-P3 manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, Germany.	The appliances must be fitted with a mechanical stop to the air control to prevent closure beyond the 10mm open position.	organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Vista Magnifico SE NS-1 and Vista Perfetto SE NS-2 4.9kW multi-fuel stoves manufactured by Newman Fireplaces Ltd, Units 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.	Installation and user instruction manual dated 3rd June 2014, reference "NS-1, NS-2 Edition: 2".  The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Volan 750 Glass and Vega 75-Glass 7.5kW multifuel stove manufactured by F.E. Robinson (Hooton) Limited, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	Instruction manual dated 28th July 2015, reference: "Triton 450 / Vega 450 / Volan 750 / Vega 750 Solid Fuel Stoves Manual Version 1.1 Issued 28/07/2015."	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result

(1) Class of fireplace	(2) Conditions	
бузисрисс	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels): of treatment with woodpreservatives or coatings.
Wiking Miro 1,2,3,4,5 and 6 4.9kW wood-burning stoves manufactured by HWAM Heat Design AS, Nydamsvej 53, 8362 Hørning, Denmark.	2013 reference "IN1274 Ed A".  Fitted with a mechanical stop to prevent air control closure	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Woody 5kW multifuel stove manufactured by Chilli Penguin Stoves Limited, Castell Bach, Mynydd Nefyn, Pwllheli, LL53 6TL.	Installation and Operating Instructions manual dated June 2015 reference "CPS 9768".  The appliance must be fitted with a mechanical stop to prevent closure of the secondary air controller beyond 18mm from the closed position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Zaragoza model F9437,	Installation and Operation Manual dated 27th July 2015 reference "ZARAGOZA – Version A".	Wood logs. The fuel must not
Granada model F9437 G, Zaragoza Exclusive model F9437 E, Zaragoza Plus model	The appliance must be fitted with a modified air regulator which has a permanent opening of 388mm <sup>2</sup> when in the fully closed position.	contain halogenated organic compounds or heavy metals as
F9437 P,		a result of treatment with wood-

(1) Class of fireplace	(2) Conditions	
бузпершсе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	Permitted fuels (other than authorised fuels):
Zaragoza Top model F9437 T,		preservatives or coatings.
Zaragoza Box model F9437 B,		
Caen ceramic model F9437 C and		
Caen soapstone model F9437 S 5kW multifuel stoves manufactured by THORMA Vyroba k.s., Šavol'ská cesta 323/1, 986 01, Fil'akovo- Priemyselný obvod, Slovakia.		

## **EXPLANATORY NOTE**

(This note is not part of the Regulations)

The Smoke Control Areas (Exempted Fireplaces) (No.2) Regulations (Northern Ireland) 2013 ("the 2013 Regulations") specify those fireplaces exempted from the provisions of Article 17(7) of the Clean Air (Northern Ireland) Order 1981 ("the 1981 Order").

Article 17 of the 1981 Order generally prohibits the emission of smoke from chimneys in smoke control areas. However, under paragraph 7 of Article 17 of the 1981 Order, the Department of the Environment may exempt certain classes of fireplaces from the provisions of Article 17 of the 1981 Order, if it is satisfied that they can be used for burning fuel other than authorised fuels, without producing any smoke, or a substantial quantity of smoke.

These Regulations amend the 2013 Regulations to include a number of additional fireplaces to the Schedule that have been tested and found to be suitable for use in smoke control areas. There are also amendments to the details of some existing fireplaces.