STATUTORY INSTRUMENTS

2012 No. 244 (W.38)

CLEAN AIR, WALES

The Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2012

Made - - - - 1 February 2012
Laid before the National
Assembly for Wales - - 2 February 2012
Coming into force - - 27 February 2012

The Welsh Ministers in exercise of the powers conferred upon the Secretary of State by section 21 of the Clean Air Act 1993(1) and now vested in the Welsh Ministers(2) so far as exercisable in relation to Wales, and being satisfied that the fireplaces exempted by this Order can be used for burning fuel other than authorised fuels without producing any smoke or a substantial quantity of smoke, hereby make the following Order:

Title, commencement and application

- 1.—(1) The title of this Order is the Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2012 and it comes into force on 27 February 2012.
 - (2) This Order applies in relation to Wales.

Fireplaces exempted from section 20 of the Clean Air Act 1993

2. The fireplaces described in the Schedule are, subject to the conditions listed, exempted from the provisions of section 20 of the Clean Air Act 1993 (which prohibits smoke emissions in smoke control areas).

Revocation

3. The Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2011(3) is revoked.

^{(1) 1993} c. 11.

⁽²⁾ The relevant functions of the Secretary of State were, so far as exercisable in relation to Wales, transferred to the National Assembly for Wales by virtue of article 2 of, and Schedule 1 to, the National Assembly for Wales (Transfer of Functions) Order 1999 (S.I. 1999/672). Those functions are now exercisable by the Welsh Ministers by virtue of section 162 of, and paragraph 30 of Schedule 11 to, the Government of Wales Act 2006 (c. 32).

⁽³⁾ SI 2011/38 (W.13)

John Griffiths
Minister for Environment and Sustainable
Development, one of the Welsh Ministers

1 February 2012

SCHEDULE

Article 2

EXEMPTED FIREPLACES

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| 18i and 60i stoves. Manufactured by Jetmaster Fires Ltd, Unit 2 Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT. | Installation and use instruction manual reference: "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference: "Part No 106872 Issue No. 1" dated May 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 40% open position. | Wood logs . |
| Aarrow Signature 5 SC; Aarrow Ecoburn 5 SC; Hamlet Solution 5 SC; Villager Espirit 5 SC. Manufactured by Arada Ltd, The Fire Works, Millwey Industrial Estate, Axminster, Devon, EX13 5HU. | Instruction manual reference "Rev 02" dated April 2010. All the appliances must be fitted with a mechanical stop to prevent closure of the air control beyond 20mm from the closed position and 50 mm beyond the fully open position. | Wood logs . |
| Aduro 3D, 8D, 10D, 11D and Asgård 1D, 2D and 7D wood burning stoves. Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business | Instruction manual reference "Pexex1001/AH/ver1" and dated June 2011. It must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively. | Dry wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1)

⁽¹⁾

<u>(1)</u>

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Park, Waldringfield, Ipswich, IP12 4PS. | | |
| Aduro 9D wood burning stove. | Instruction manual reference "Pevex1002/AH/ver1" and dated June 2011. | Dry wood logs . |
| Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS. | It must be fitted with permanent stops to ensure that ensure the primary and secondary air controls do not close beyond 95% and 50% respectively. | |
| Arimax Bio 300kW; Arimax Bio 400kW; Arimax Bio 500kW. | Instruction manual reference "INSTALLATION AND OPERATION MANUAL Arimax Bio 120-3000 kW" dated 30/03/2010. | 6—8mm wood pellets with a moisture content less than 10%. |
| Manufactured by Artierm Oy, Kimmo Kantalainen; PO Box 59; Fin - 43101; Saarijärvi, Finland. | 30/03/2010. | |
| Ashwell Green-Tec 150 boiler. | Instruction manual reference "ASH-gt150/101 Version 1.2" dated 06/2009. | Wood pellets . |
| Manufactured by Ashwell Biomass Ltd, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT. | | |
| Ashwell Green-Tec 195 boiler. | Instruction manual reference "ASH-gt195/102 Version 1.2" dated 06/2009. | Wood pellets . |
| Manufactured by Ashwell Biomass Ltd, | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT. | | |
| Ashwell Green-Tec 300 boiler. | Instruction manual reference "ASH-gt300/103 Version 1.2" dated 06/2009. | Wood pellets . |
| Manufactured by Ashwell Biomass Ltd, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT. | | |
| Barbas ECO 40, 5 kW wood burning roomheater. | ECO 40 instruction manual, document Version 01-327332 dated October 2009. | Wood logs . |
| Manufactured by Interfocos BV; Hallenstraat 17, NL-5531 AB, BLADEL, Netherlands. | | |
| Barbas ECO 52 Stove. Manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands. | Instruction manual reference "02 - 327332" dated March 2010. | Wood logs . |
| Barbas Unilux — 3 40, 5kW wood burning insert. | Unilux — 3 40 instruction manual, document Version 01 - 326587 dated August 2009. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1

(1)

(1)

<u>(1)</u>

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Manufactured by Interfocos BV, Hallenstraat 17, NL — 5531 AB, BLADEL, Netherlands. | | , |
| Barbas Unilux 3- 52 Stove. | Instruction manual reference "03 - 326587" dated March 2010. | Wood logs . |
| Manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands. | | |
| Baxi Bioflo. | Operating instruction manual reference "720574401" dated 2010 and installation | Wood pellets . |
| Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria. | and servicing instruction manual reference "720574501" dated 2010. | |
| Be Modern Monroe 5, Monroe 5, Be | Instruction manual reference "OCT10/GB" dated 6th October 2010. | Wood logs . |
| Modern Monterrey 5, Monterrey 5 and York Midi Multi Fuel Stoves. | The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8mm open position. | |
| Manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|-----------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| • | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Be Modern Monterrey 7, Monterrey 7, Be Modern Monroe 7 and Monroe 7 Multi Fuel Stoves. | Instruction manual reference "OCT10/GB" dated 6th October 2010. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to be less than 10mm open position. | Wood logs . |
| Manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB. | | |
| The Binder Wood Fired Boiler models RRK 22 — 49 (49 kW output). | The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0. | Wood pellets or wood chips . |
| Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria. | | |
| The Binder Wood Fired Boiler models RRK 80 — 175 (75 — 149 kW output) with cyclone models ZA 80 — 175. | The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0. | Wood pellets or wood chips . |
| Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Mitterdorfer Strasse 5, A-8572 Barnbach, Austria. | | |
| The Binder Wood Fired Boiler model RRK 130 — 250 (185 — 230 kW output) 200-350 (250-300kW output) 400-600 (350-500 kW output) 640-850 (650-840kW output) with cyclone (model type ZA). | The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0. | Wood pellets or wood chips . |
| Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria. | | |
| The Binder Wood Fired Boiler model RRK 1000 (1200 kW output) with multi- cyclone (model MZA). | The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0. | Wood pellets or wood chips . |
| Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| The Binder Wood Fired Boiler model RRK 1200-1650 with Binder model MZA multi-cyclone and automatic ignition. | The manufacturer's and Wood Energy Limited's operating instructions for Binder appliances reference "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8", dated 15 July 2009. | Wood pellets or wood chips . |
| Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria. | | |
| The Binder Wood Fired Boiler model RRK 1800-2300 with Binder model MZA multi-cyclone and automatic ignition. | The manufacturer's and Wood Energy Limited's Operating instructions for Binder appliances reference: "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8", dated 15 July 2009. | Wood pellets or wood chips . |
| Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria. | | |
| The Binder Wood Fired Boiler model RRK 2500-3000 with Binder model MZA multi-cyclone and automatic ignition. | The manufacturer's and Wood Energy Limited's Operating instructions for Binder appliances reference: "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8", dated 15 July 2009. | Wood pellets or wood chips . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria. | | |
| The Biomatic 220 and 250 fitted with Zyklovent 220-250 cyclone separator. | The manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc. | Wood chips, wood pellets, or planed wood shavings. |
| Manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria. | | |
| The Biomatic 300, 350, 400 and 500 fitted with Zyklovent 300-500 cyclone separator. | The manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc. | Wood chips, wood pellets, or planed wood shavings. |
| Manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ, Feuerungstechnik, A-8272 Sebersdorf 138, Austria. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Boru 4.9kW Stove. Manufactured by Righpur Ltd, T/A Boru Stoves, The Hive, Ballydine, Gooldscross, Ireland. | The Instruction manual reference "BFF010" dated 26/01/2011. The air controls must be fixed such they cannot be closed more than: — Primary air slide 2mm; — Secondary air slide 2mm; — Tertiary air slide 30%. | Wood logs . |
| Burley Hollywell SE. Manufactured by Burley Appliances Ltd., Lands End Way, Oakham, Rutland, LE15 6RB. | The instruction manual reference "BUR/11/05" dated January 2011. The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm. | Wood logs. |
| Bushman Large Commercial Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd, | The Instruction manual reference "LCOINST" dated 01/2011. | Wood logs . |
| PO Box 3534, Kidderminster Worcestershire, DY14 9ZE. | | |
| Bushman Large Domestic Pizza Oven. Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster | The Instruction manual reference "LDOINST" dated 01/2011. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1

(1)

(1)

ìή

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Worcestershire, DY14 9ZE. | | |
| Bushman Medium Commercial Pizza Oven. | The Instruction manual reference "MCOINST" dated 01/2011. | Wood logs . |
| Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE. | | |
| Bushman Medium Domestic Pizza Oven. | The Instruction manual reference "MDOINST" dated 01/2011. | Wood logs . |
| Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE. | | |
| Bushman Small Commercial Pizza Oven. | The Instruction manual reference "SCOINST" dated 01/2011. | Wood logs . |
| Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Bushman Small Domestic Pizza Oven. | The Instruction manual reference "SDOINST" dated 01/2011. | Wood logs . |
| Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE. | | |
| Carillon 4:3. | The Instruction manual reference "7196755-Rev.09" dated 22nd December 2010. | Wood logs . |
| Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position. | |
| Carillon 16:9 Crystal. | The Instruction manual reference "7196755-Rev.09" dated 22nd December 2010. | Wood logs . |
| Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position. | |
| Carron Dante SE. | The Instruction manual reference "BHC401-406" dated 12th January 2011. | Wood logs . |
| Manufactured by JIG UK Ltd, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL. | The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 14mm. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Carron Stove. Manufactured by JIG UK Ltd, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL | The Instruction manual reference "91-62351" dated July 2009. | Dry and split wood logs of a maximum length of 23cm. |
| Carron Stove SE. Manufactured by JIG UK Ltd, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL. | Instruction manual reference "BHC501-506" dated 12th January 2011. The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 3mm. | Wood logs . |
| Charnwood Country 4 wood burning stove. Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS. | The modification instruction manual reference "TIS.95" dated 01/2011 and instruction manual "Country 4 MKII" dated 01/2011. The appliance must be fitted with the manufacturer's smoke reduction kit to fix the minimum aperture of the secondary air inlets to a minimum of 21mm open. | Wood logs . |
| Charnwood Cove 1SR. Manufactured by A.J. Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS. | Installation and use instruction manual reference "COVE1SR01.10 Issue A". The air control must be adjusted such that the minimum closure of the air control is equivalent to that found with the control pushed in 15mm from the fully open position. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Charnwood Island 1. Manufactured by | The Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010. | Wood logs . |
| A.J. Wells and Son Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS. | It must be fitted with a stop bracket (Kit No. 010/AY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm. | |
| Charnwood Island 2; | The Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010. | Wood logs . |
| Manufactured by A.J. Wells and Son Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS | It must be fitted with a stop bracket (Kit No. 010/BY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm. | |
| Charnwood Island 3. | The Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010. | Wood logs . |
| Manufactured by A.J. Wells and Son Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS. | It must be fitted with a stop bracket (Kit No. 010/CY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm. | |
| Charnwood Tor stove. Manufactured by A.J. Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS. | Installation and use instruction manual reference "Tor 02.10 Issue A". | Wood logs . |
| Charnwood Tor Pico. | The Instruction manual reference "Tor & Tor | Wood logs . |
| Manufactured by A.J. Wells and Son | Pico 12.10 IssueB" dated December 2010. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1)

(1)

(1)

(1)

| Fireplace | Conditions | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS | | |
| Chesneys 4 Series (4.6kW) Stoves: Flatford 4; Hampstead 4, Alpine 4 also sold as: Sunbeam 4, Dakota 4, Providence 4, Pacific 4 also sold as: Milan 4, Murano 4, Apollo 4, Chelsea 4 also sold as: Wellington 4, Guernsey 4, Belgravia 4. | The Chesneys 4 series instruction manual reference "CH4K-V4" dated 7 December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 34mm open position. | Wood logs . |
| Manufactured by Chesneys Ltd, 194-200 Battersea Park Road, London, SW1 14ND. | | |
| Chesneys Series 6 (7kW) Stoves: Flatford 6, Petworth 6, Barrington 6, Hampstead 6, Alpine 6 also sold as: Sunbeam 6, Dakota 6, Providence 6; Chelsea 6 also sold as: Wellington 6, Guernsey 6, Belgravia 6. | The Chesneys 6 series instruction manual reference "CH6K-V4" dated 7 December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 10mm open position. | Wood logs . |
| Manufactured by Chesneys Ltd, 194-200 | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Battersea Park Road, London, SW1 14ND. | | |
| Classic model 25, 35, 40, 49 and 60 wood pellet boilers. | The manufacturer's installation manual for the Classic Pellet Boilers reference "No. 22, Pellet Boilers, Type Classic 25, 31, 35, 40, 49, 60, reference BA Classic 25L-60L Nr 21 0508". | Wood pellets . |
| Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria. | | |
| Clean Air Systems CAS 200, 400 and 600 hand-fed airheaters. | The Handbook for CAS hand fired airheater range reference 24600H version 1 dated January 2011. | Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts. |
| Manufactured by Inventair Ltd, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY. | | empoourd officials. |
| Clean Air Systems CAS 300 Max airheater and cyclone. | The Handbook for CAS 300 Max airheater range reference 300A version 1 dated January 2011. | Chipped or sawdust softwood, hardwood, medium density |
| Manufactured by Inventair Ltd, Lancaster Road, Carnaby Industrial Estate, Bridlington, | | fibreboard (MDF) or chipboard. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| East Yorkshire, YO15 3QY. | | |
| The Clearview Pioneer 400, Solution 400 and Pioneer Oven wood burning stoves. | The manufacturer's instructions entitled "Operating Instructions Clearview Vision/ Vision Inset/Pioneer & Solution" dated 1 July 2006, reference V1/42, stamped and signed "Smoke Control". | Air-dried wood logs . |
| Manufactured by Clearview Stoves, More Works, Bishops Castle, Shropshire, SY9 5HH. | The appliance must be fitted with a tamperproof mechanical stop on the air slide/damper. | |
| Contura 510, 520T, 550, 550A, 550W, 560T, 560K, 570, 580, 585, 590, Contura T. | The manufacturer's installation instructions IAV SE/EX 0726-6 611821 Lighting instruction BAV SA/EX 0717-2 611820. | Untreated dry wood with less than 20% moisture. |
| Manufactured by Nibe AB, Box 134, 285 23 Markaryd, Sweden. | A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position. | |
| Contura 580W. | The manufacturer's installation instructions IAV SE/EX 0740-1 511911. | Untreated dry wood with less than 20% |
| Manufactured by Nibe AB, Box 134, 285 23 Markaryd, Sweden. | A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position. | moisture. |
| Contura 750, 750A; and 780. | Instruction manual reference "811064 BAV SE-EX C750/780-1". | Wood logs . |
| Manufactured by Nibe AB, Box 134, 285 23 Markaryd, Sweden. | The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| - | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Contura i4 Modern and Contura i4 Classic. | The Instruction manual reference "811136 BAV C i4 GB-1" dated 04-07-2011 and supplementary operating instructions "811142 BAV GB-2" dated June 2011. | Dry wood logs . |
| Manufactured by Nibe AB, Box 134, 285 23 Markaryd, Sweden. | It must be fitted with a mechanical stop to prevent closure beyond the 28% open position. | |
| Cove 2 SR. Manufactured by A.J. Wells and Son Ltd. Of Rishons Way | The manufacturer's instruction manual reference "Cove2SR 07.09 IssB" dated July 2009. A permanent stop must be in place on air | Dry and split wood logs of a maximum length of 23cm. |
| Ltd. Of Bishops Way, Newport, Isle of Wight, PO30 5WS | control to prevent closure beyond 14mm from the fully closed position. | |
| CTC Ecoflex 15 and 20. | The manufacturer's instructions dated 20 February 2007, reference 161 505 27 06/1. | Wood pellets . |
| Manufactured by Enertech AB, Box 313, S-341 26 Ljungby, Sweden. | | |
| Dimplex SE Selbourne 5. | The Instruction manual reference "SE Selbourne 5 Issue 1" dated 08 2009. | Wood logs . |
| Manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN. | All appliances must be fitted with a mechanical stop to prevent closure beyond the 50% open position. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| The Dovre 250 (model DV-250). | The manufacturer's instructions, reference "PM250 Issue 1". | Untreated dry wood . |
| Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium. | A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position. | |
| The Dunsley Yorkshire Stove. | The manufacturer's instructions dated 5 August 1998, reference A/22160 as amended by those | Untreated dry wood; |
| Manufactured by Dunsley Heat Ltd, Bridge Mills, | dated 4 December 2004, reference D13. | Peat or peat briquettes with, in either case, less than 25% moisture; |
| Huddersfield Road, Holmfirth, Yorkshire HD9 3TW. | | Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight; |
| | | CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Тиерисе | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| | | and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight. |
| | The manufacturer's instructions dated 5 August | Untreated dry wood; |
| Multifuel Stove. Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire HD9 3TW. | 1998, reference A/22160 as amended by those dated 4 December 2004, reference D13. | Peat or peat briquettes with, in either case, less than 25% moisture; |
| | | Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight; |
| | | CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1)

| Fireplace | Conditions | |
|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| | | coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight. |
| The Dunsley Yorkshire Multifuel Stove and | The manufacturer's instructions dated 5 August 1998, reference A/22160 as amended by | Untreated dry wood; |
| Multifuel Stove and Boiler. Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire HD9 3TW. | those dated 4 October 2004, reference GHD/DUN4B/1. | Peat or peat briquettes with, in either case, less than 25% moisture; |
| | | Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight; |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | and the following fuel or fuels: CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of |
| The Dunsley Yorkshire Woodburning Stove. | The manufacturer's instructions dated 4 December 2004, reference D13W. | the total weight. Untreated dry wood. |
| Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire HD9 3TW. | | |
| The Dunsley Yorkshire Woodburning Stove and Boiler . | The manufacturer's instructions dated 4 December 2004, reference D13W together with the manufacturer's instructions dated 4 October 2004, reference GHD/DUN4B/1. | Untreated dry wood. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire HD9 3TW. | | |
| Earlswood. | The Instruction manual reference "EW1MF technical manual" dated 02 2009. | Wood logs . |
| Manufactured by ACR Heat Products Ltd, Unit One Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP. | When the primary air control is in the closed position, it must remain permanently open by 5mm and be prevented from closing fully by a screw. | |
| Ecco Stove E678. | The Instruction manual reference "01/11/3" dated 28/01/2011. | Wood logs . |
| Manufactured by Landy Vent UK Ltd, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX. | The appliance must be fitted with a system to fix the secondary air (airwash) to a 4mm open position. | |
| Ecco Stove E850. | The Instruction manual reference "02/10" dated 10th October 2010. | Wood logs . |
| Manufactured by Landy Vent UK Ltd, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX. | The appliance must be fitted with a system that prevents closure of the secondary air flaps beyond 4mm (3 turns). | |
| Eco-Ideal Eco 1 Stove. | The Instruction manual reference "JINECO01 revC" dated 20/07/11. | Dry wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ. | It must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30%open. | |
| Eco-Ideal Eco 2 Stove. | The Instruction manual reference "JINECO02 revC" dated 20/07/11. | Dry wood logs . |
| Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ. | It must be fitted with a permanent stop that prevents closure of the secondary air slider | |
| Eco-Ideal Eco 4 Stove. | The Instruction manual reference "JINEC004 revC" dated 20/07/11. | Dry wood logs . |
| Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ. | Teve dated 20/07/11. | |
| Eco-Ideal Eco 6 Stove. Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ. | The Instruction manual reference "JINEC006 revC" dated 20/07/11. | Dry wood logs . |
| Ellipse. | The Instruction manual reference "7196901-Rev.09" dated 22nd December 2010. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1

⁽I)

⁽¹⁾

<u>(1)</u>

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | It must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position. | |
| Endress USF-W 250. Manufactured | The Instruction manual reference "Operating and Maintenance manual Endress USF -W250" dated 03/2010. Reference EMAN - USFW250. | Wood chips and pellets |
| by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim. | and 35, 2010. Reserved Emilia Cost W250. | |
| Endress USF-W 350. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim. | The Instruction manual references "Operating and Maintenance manual Endress USF -W350" dated 03/2010. Reference EMAN - USFW350. | Wood chips and pellets . |
| Endress USF-W 500. | The Instruction manual references "Operating and Maintenance manual Endress USF -W500" | Wood chips and pellets . |
| Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim. | dated 03/2010. Reference EMAN - USFW500. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Endress USF-W 800. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim. | The Instruction manual references "Operating and Maintenance manual Endress USF -W800" dated 03/2010. Reference EMAN - USFW800. | Wood chips and pellets . |
| Endress USF-W 1000. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim. | The Instruction manual reference "Operating and Maintenance manual Endress USF - W1000" dated 03/2010. Reference EMAN - USFW1000. | Wood chips and pellets . |
| Endress VR-S 300. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim. | The Instruction manual reference "Operating and Maintenance manual Endress VR-S300" dated 03/2010. Reference EMAN - VRS300. | Wood chips and pellets |
| Endress VR-W 400. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze | The Instruction manual reference "Operating and Maintenance manual Endress VR -W400" dated 03/2010. Reference EMAN - VRW400. | Wood chips and pellets |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1)

(1)

(1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| 18, D-91593 Burgbernheim. | | |
| Endress VR-W 600. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 | The Instruction manual reference "Operating and Maintenance manual Endress VR-W600" dated 03/2010. Reference EMAN - VRW600. | Wood chips and pellets . |
| Burgbernheim. Endress VR-W 900. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim. | The Instruction manual reference "Operating and Maintenance manual Endress VR-W900" dated 03/2010. Reference EMAN - VRW900. | Wood chips and pellets . |
| En-tech model ENP 10, 15, 18, 25 and 35 boilers | The manufacturer's installation manual dated 11/2009, reference IMENP 10-35 11/2009 for the Firefox pellet boiler. | Wood pellets . |
| Manufactured by En-tech Energietechnikpproduk Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria. | tion, | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| En-tech model PK15 and 25 boilers Manufactured by En-tech Energietechnikpprodukt Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria. | The manufacturer's installation manual dated 11/2009, reference IMPK PK 15/25 11/2009 EN for the Firefox pellet boiler. | Wood pellets . |
| En-tech model PK45 boilers Manufactured by En-tech Energietechnikpprodukt Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria. | The manufacturer's installation manual dated 11/2009, reference IMPK PK 45 11/2009 EN for the Firefox pellet boiler. | Wood pellets . |
| | The use and maintenance manual reference "Uniconfort EOS30 Manual v1" dated July 2011. | Wood pellets . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The use and maintenance manual reference "Uniconfort EOS35 Manual v1" dated July 2011. | Wood pellets . |
| Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy. | | |
| | The use and maintenance manual reference "Uniconfort EOS40 Manual v1" dated July 2011. | Wood pellets . |
| Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy. | | |
| EOS 60 700 kW output wood pellet boiler with multicyclone. | The installation instruction manual reference "K135-07332 Uniconfort MUN v 2" dated September 2010. | 6mm diameter wood pellets . |
| Manufactured by Uniconfort srl. Via dell'Industria 21, 35018, San Martino Di Lupari, (PD) Italy. | | |
| ESSE 100 SE Smoke Exempt woodburning stove. | Manufacturer's instruction manual dated February 2009, reference 100 SE Issue 1. | Untreated dry wood with a maximum moisture content of 20% maximum |
| Manufactured by ESSE Engineering | | length of 200 mm and |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Ltd., Ouzledale Foundry, Long Ing, Barnoldswisk, Lancashire, BB18 6BN, | | maximum width or diameter of 120 mm. |
| ESSE 125 SE. | Instruction manual reference "Esse 125SE Issue 1" dated 08 2009. | Wood logs . |
| Manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN. | The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position. | |
| Esse 301 SE stove. | The Instruction manual reference "v45" dated 09/11/2010. | Wood logs . |
| Manufactured by Esse Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN. | The primary air control must not be fully air tight when closed. | |
| Esse 350 stove. | The Instruction manual reference "v45" dated 09/11/2010. | Wood logs . |
| Manufactured by Esse Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Esse 1622 inset stove. Manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN. | Installation and operation manual reference "1622/Integra INSET revision c" dated July 2010. The appliance must be fitted with a mechanical stop to fix secondary air control fully open. | Dry wood logs . |
| ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers. | The Instruction manual reference "HACK20-200_Bedienung_2011-06_EN" dated 06/2011. | Wood chips . |
| Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria. | An integrated flue gas recirculation system must be used when using wood chips with a moisture content below 15%. | |
| ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers. | The Instruction manual reference "HACK20-200_Bedienun 2011-06_EN" dated 06/2011. | Wood pellets . |
| Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria. | An integrated flue gas recirculation system must be used when burning wood pellets. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| ETA PC 20, 25 and 32 wood pellet boilers. Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria. | The Instruction manual reference "PC20-32_Bedienung_2011-06_EN" dated 06/2011. | Wood pellets . |
| ETA PE-K 35, 50, 70 and 90 wood pellet boilers. | The Instruction manual reference "PE-K35-90_Bedienung_2011-06_EN" dated 06/2011. | Wood pellets . |
| Manufactured by ETA Heiztechnik GmbH, Christian Malecz, ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria. | | |
| ETA PU 7, 11 and 15 wood pellet boilers. | The Instruction manual reference "PU7-15_Bedienung_2011-06_EN" dated 06/2011. | Wood pellets . |
| Manufactured by ETA Heiztechnik GmbH, Gesellschaft mit beschrankter Haftung (GmbH), | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria. | | |
| ETA SH 20, 30, 40, 50 and 60 wood gasification boilers. | The Instruction manual reference "SH20-60_Bedienung_2011-06_EN" dated 06/2011. | Wood logs . |
| Manufactured by ETA Heiztechnik GmbH, Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria. | | |
| eVolution 5 model number M-EVO5. | The Instruction manual reference "eVo 5 MS07-11" dated 8th July 2011. | Wood logs . |
| Manufactured by; Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park Shrewsbury, Shropshire, SY1 3AB. | The appliance must be fitted with a system that prevents the closure of the air control to less than 70% open. | |
| Evotherm P50, P100, P120, P150, P170, P200 pellet boilers. | The manufacturer's instructions "Operating manual" reference "Version 1/2010/Rev. 4.21". | Wood pellets . |
| Manufactured by Evotherm, Heiztechnik Vertriebs Gesellschadft mit beschrankter Haftung (GmbH), | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Seeleiten 24, AT 5120, St Pantaleon, Austria. | | |
| The Extraflame: Babyfiamma, Bella and Bella Lux, Clementina Comfort Maxi, Contessa, Divina, Divina Plus and Divina Steel, Duchessa and Duchessa Steel, Ecologica, Esmeralda and Esmeralda Crystal, Falò 1CP, Falò 2CP and Falò 1XP, Isabella, Karolina, Preziosa. | The manufacturer's instructions dated 5 March 2007, reference 004275101 011. | Wood pellets . |
| Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy. | | |
| The Extraflame Comfort Mini. | The manufacturer's instructions dated 2 October 2006, reference 004275115 REV 005. | Wood pellets . |
| Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy. | | |
| The Extraflame Idro. Manufactured by Extraflame S.p.a in | The manufacturer's instructions dated 28 August 2006, reference 004275128 REV 002. | Wood pellets . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Montecchio Precalcino (Vicenza), Italy. | | |
| The Extraflame Lucrezia Idro and Lucrezia Steel. | The manufacturer's instructions dated 12 July 2006, reference 004275110 REV 011. | Wood pellets . |
| Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy. | | |
| Fireball. | The Instruction manual reference "7196801-Rev.07" dated 22nd December 2010. | Wood logs . |
| Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position. | |
| Firefox 5 Clean Burn II, Gallery Classic 5 Clean Burn, Sirius 405 | The Instruction manual reference "FF5CBII REV:A" dated June 2011. | Dry wood logs . |
| Clean Burn and Sirius 405 Classic Clean Burn. | It must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position. | |
| Manufactured by Percy Doughty & Co Ltd, Imperial Point, Express Trading Estate Stone Hill Road, Farnworth, Bolton, BL4 9TN. | | |
| Firefox 5CB (4.9kW); Vega 100CB (4.9kW); | The Instruction manual reference "FFXCBA" dated January 2010. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾

⁽¹⁾

 $^{^{(1)}}$

⁽¹⁾

Fireplace Conditions The fireplace must be installed, maintained No fuel is to be used and operated in accordance with the in the fireplace other following specifications: than authorised fuels and the following fuel or fuels: Sirius 405CB (4.9kW); Flame 5CB (4.9kW). Manufactured by Percy Doughty & Co, Imperial Point, **Express Trading** Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN. Firefox 8 Clean Burn, The Instruction manual reference "FF8CB Dry wood logs. Gallery Classic 8 REV:A" dated June 2011. Clean Burn, Sirius 545 Clean Burn and Sirius It must be fitted with a mechanical stop to 545 Classic Clean prevent secondary air closure beyond the 50% Burn. open position. Manufactured by Percy Doughty & Co Ltd, Imperial Point, **Express Trading Estate** Stone Hill Road, Farnworth, Bolton, BL4 9TN. Fireline FXi 5kW; The Instruction manual reference "Issue 03" Wood logs. Fireline FPi 5kW; dated 03/10. Fireline FX5; Fireline FP5. The appliance must be fitted with a system that prevents the closure of the secondary air Manufactured control beyond the 3.5mm open position. by Charlton and Jenrick Ltd, G1-G2 Halesfield 5, Telford, Shropshire, TF7 4QJ. The fuel must not contain halogenated organic compounds or heavy metals as a

(1)

result of treatment with wood-preservatives or

coatings.

⁽¹⁾

| The fireplace must be installed, maintained | No fuel is to be used |
|-----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| and operated in accordance with the following specifications: | in the fireplace other than authorised fuels and the following fuel or fuels: |
| The manufacturer's instructions dated June 2005, reference "Bedienungsanleitung Firematic V 1.1 ENG doc". | Chipped wood, wood pellets, or planed wood shavings . |
| Instruction manual reference "05.007 Operating Instructions — FM (1Ph) 20 35 45 60 v2.3" dated "08/2009". | Wood pellets conforming to ÖNORM M7135 with diameter of 6mm or wood chips up to a maximum size of 50mm and maximum water content 35%. |
| The Savoy EA Technical Manual, document reference 1290-1, reviewed 9 July 2009. | Wood logs . |
| | |
| | The manufacturer's instructions dated June 2005, reference "Bedienungsanleitung Firematic V 1.1 ENG doc". Instruction manual reference "05.007 Operating Instructions — FM (1Ph) 20 35 45 60 v2.3" dated "08/2009". The Savoy EA Technical Manual, document |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Fröling Lambdamat commercial wood chip boiler models 500,750 and 1000. | The "Lambdamat communal Operating and Installation Manual" reference B 069 01 04 of February 2004. | Wood chips . |
| Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria. | | |
| Fröling P4 8, 15, 20, 25, 32, 38, 48 and 60 Pellet Boilers. | The manufacturer's instruction manual reference "BO430408 _en" dated July 2009. | Wood pellets with a diameter of 6mm. |
| Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria. | | |
| Froling S4 Turbo 15 15kW; Froling S4 Turbo 22 22kW; Froling S4 Turbo 28 28kW; Froling S4 Turbo 34 34kW; Froling S4 Turbo 40 40kW; Froling S4 Turbo 50 50kW; and Froling S4 Turbo 60 60kW. | The Assembly Instruction manual "M0970208" dated November 2008 and Operating instruction manual "B0510108" dated November 2008. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Manufactured by Froling Heizkessel und Behalterbau Ges. M.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria. | | |
| The Fröling Turbomatic 28, 35, 48 and 55 | The fireplace must be installed in accordance with the manufacturer's installation instructions dated November 2003, reference M 060 01 03. | Wood chips with less than 35% moisture content that meet ONORM (a) M 7133: |
| Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria. | The fireplace must be maintained and operated in accordance with the manufacturer's instructions dated August 2002, reference 99229a. | ÖNORM (a) M 7133: 1998 size class G30 or wood pellets of 6mm diameter and a moisture content below 10%. |
| The Fröling Turbomatic 85, 100 and 110 | The fireplace must be installed in accordance with the manufacturer's installation instructions dated November 2003, reference M 060 01 03. | Wood chips with less than 35% moisture content that meet ÖNORM (a) M 7133; |
| Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria. | The fireplace must be maintained and operated in accordance with the manufacturer's instructions dated August 2002, reference 99229a. | or G50, wood pellets of 6mm diameter and a moisture content below 10%. |
| The Fröling Turbomat 150 and 220 | The manufacturer's instructions dated August 2003, reference BO310003. | Wood pellets, or wood chips . |
| Manufactured by Fröling Heizkessel-und Behälterbau | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria. | | |
| The Fröling Turbomat 320 and 500 | The manufacturer's instructions dated November 2004, reference B0340004. | Wood pellets, or wood chips . |
| Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria. | | |
| Fröling TX150 150kW boiler with Exhaust Gas Recirculation device. | The Installation Instruction manual reference "M1130009" dated 09/2010 and operating instruction manual "B 067 00 09" dated 09/2010. | Wood chips with a moisture content ≤30% and a maximum cross sectional area of 5cm2 or wood pellets with a moisture |
| Fröling Heizkessel- und Behälterbau, Ges.m.b.H., Industriestrasze 12, Austria. | | content of ≤10% and a maximum diameter of 10mm. |
| The Gilles HPK-RA 13 kW, 15 kW, 20 kW, 25 kW, 30 kW, 35 kW, 40 kW, 45 kW, 49 kW, 60 kW, 70 kW, 75 kW, 85 kW, 95 kW, 100 kW, 120 kW, and 145 kW, | The manufacturer's instructions dated January 2007, reference Gilles/0-145/1. | Wood pellets, or wood chips . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria. | | |
| Gilles HPK-RA 160. Manufactured by Gilles Energie - und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria. | The instruction and operating manuals "BD-200-01a-01" and dated 11/2008, "BD-200-01a-02" and dated 11/2008, "BD-200-01a-03" and dated 11/2008, "BD-200-01a-04" and dated 11/2008, "BD-200-01a-06" and dated 11/2008, "BD-200-03a-07" and dated 11/2008, and "BD-200-03a-09" and dated 11/2008. | Wood chips and pellets |
| The Gilles HPK USK 150 kW, 180 kW, 240 kW and 300 kW | The manufacturer's instructions dated January 2007, reference Gilles/150-300/1. | Wood pellets, or wood chips . |
| Manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria. | | |
| The Gilles HPK USK 360 kW | The manufacturer's operating instructions dated January 2008, reference Gilles 360/1. | Wood pellets or wood chips . |
| Manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Gilles HPKI-K 180 and 240, 300, 360, 450, 550, 700, 900, 1200 and 1600. | The Instruction manual reference "Operating Instruction HPKI-K Underfeed Stoking. 1-general-hpki-k underfeed stoking" dated 11/2008. | Wood chips and pellets |
| Manufactured by Gilles Energie - und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria. | | |
| The Gilles UTSK 450 kW, 550 kW, 700 kW, 900 kW, 1200 kW, and 1600 kW Boilers. | The manufacturer's operating instructions dated January 2008, reference Gilles 360/1. | Wood pellets or wood chips . |
| Manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria. | | |
| Guntamatic Biocom and Powercorn 50 and 75. | The manufacturer's instruction manual reference "GUN/BIO/OP/ VI/0709" dated 29/7/09. | Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm. |
| Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria. | | and 50 mm. |
| Guntamatic Powerchip 50 and 75. | The manufacturer's instruction manual reference "GUN/POW/OP/VI/0709" dated 29/7/09. | Wood pellets with a diameter of 6mm and |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by Guntamatic Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria. | | a length of between 10 and 30 mm. |
| Guntamatic Biocom and Powercorn 100. Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria. | The manufacturer's instruction manual reference "GUN/BIO/OP/VI/0709" dated 29/7/09. | Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm, or wood chip less than 35% moisture content and meeting ÖNORM M 7133:1998 size class G30. |
| Guntamatic Powerchip 100. Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria. | The manufacturer's instruction manual reference "GUN/POW/OP/VI/0709" dated 29/7/09. | Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm, or wood chip less than 35% moisture content and meeting ÖNORM M 7133:1998 size class G30. |
| Hamont CATfire 350 USZI pellet boiler fitted with CATfire 300 cyclone. | The manufacturer's operating instruction reference "Operating Manual for Boilers CATfire 150-500kW" effective from 1/1/2008. | Wood pellets with a diameter of 6mm and a maximum length of 30 mm. |
| Manufactured by Hamont Contracting and Trading, spol. s.r.o., Sedliπte 227, postal code 739 36, | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| district Frŷdek-Mistek, Czech Republic. | | |
| Handöl 31, Handöl 31A, Handöl 32, Handöl 32A, Handöl 33T, Handöl 34T, Handöl 35T,Varde Ovne Look 1, Varde Ovne Look 2, Varde Ovne Look 3. | The manufacturer's installation instructions IAV SE/EX 0811-4 511941 Lighting instructions BAV SE/EX H30 511942. A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position. | Untreated dry wood with less than 20% moisture . |
| Manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden. | | |
| Handöl 50, Handöl 51, Handöl 52, Handöl 52T, Handöl 53, Handöl 54, Handöl 54T, Handöl 51L, Varde Ovne S1, Varde Ovne S2, Varde Ovne S3. | The manufacturer's installation instructions IAV SE/EX 0737-4 511866 Lighting instructions BAV SE/EX 0717-1 511865. A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position. | Untreated dry wood with less than 20% moisture. |
| Manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden. | | |
| Harrie Leenders Cylon; Harrie Leenders Doran 160; Harrie Leenders Doran 190; Harrie Leenders Fuga S; Harrie Leenders Fuga | The Instruction manual reference "Supplementary Instructions Amended June 2010". The appliance must be fitted with a mechanical stop to prevent closure of the air slide beyond the 15mm open position. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| eL; Harrie Leenders Stor; Harrie Leenders Signa. | | |
| Manufactured by Harrie Leenders, Industrieweg 25, 5688 DP Oirschot, Netherlands. | | |
| HDG Compact models 25/35 (25 kW, 35 kW) wood chip and pellet boilers. | The manufacturer's operating instructions for the HDG Compact 25/35 with HDG Hydronic reference "HDG Compact Version V01" of April 2009. | Wood chips or wood pellets . |
| Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany. | | |
| HDG Compact models 50/65 (50 kW, 65 kW) wood chip and pellet boilers. | The manufacturer's operating instructions for the HDG Compact 50/65 with HDG Hydronic reference "HDG Compact Version V03" of April 2009. | Wood chips or wood pellets . |
| Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1)

| Finanta a | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| HDG Compact model 80 (80 kW) wood chip and pellet boiler. Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany. | The manufacturer's operating instructions for the HDG Compact 80 with HDG Hydronic reference "HDG Compact Version V03" of April 2009. | Wood chips or wood pellets . |
| HDG Compact model 100 (100 kW) wood chip and pellet boiler; HDG Compact model 150, 200 (150 kW, 200 kW) wood chip and pellet boiler with model HDG 3113 cyclone. | The manufacturer's operating instructions for the HDG Compact 100/150/200 reference "HDG Compact 100-200 Version V1" of July 2008. | Wood chips or wood pellets . |
| Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany. | | |
| HDG Euro models 30, 40 and 50 (30 kW, 40 kW and 50 kW) wood log boilers. | The manufacturer's operating instructions for the HDG Euro 30/40/50 with Lambda Control 1 reference "HDG Euro V3.0 with HDG Lambda Control 1 Version V1" of June 2008. | Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture |
| Manufactured by HDG Bavaria, Gesellschaft | 2000. | content of 20%. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany. | | |
| HDG Navaro models 20, 25 and 30 (20 kW, 25 kW and 30 kW) wood log boilers. | The manufacturer's operating instructions for the HDG Navora 20/25/30 with Lambda Control 1 reference "HDG Navora 20/25/30 with HDG Lambda Control 1 Version V2" of June 2008. | Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture |
| Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany. | | content of 20%. |
| Herz BioFire BF 500, BF 600, BF 800, and BF 1000. | The Instruction manual "Operating instructions HERZ BioFire 500 — 1000 Biocontrol" Reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc". | Wood chips and pellets . |
| Manufactured by Herz Engietechnik GmbH, Herstrabel, 7423 Pinkafeld, Austria. | Biocontrol Engliseit v 1.2.doc . | |
| Herz Firematic FM 80 and Herz Firematic FM 100. | The assembly and installation instructions "HERZ firematic 20 - 101 BioControl" Reference "04.001", installation instructions "Herz Firematic (1Ph) 20-101", as well as the | Wood chips and pellets . |
| Manufactured by Herz Engietechnik GmbH, Herstrabel, 7423 Pinkafeld, Austria. | operating instructions "HERZ firematic 20 - 101 BioControl" reference "Betriebsanleitung firematic 20-101 BioControl Englisch V 2.53.doc". | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Heta Scanline 500D, 510D, 520D and 530D wood burning stoves. | The Instruction manual reference "Pevex1005/AH/ver2" and dated June 2011. | Dry wood logs . |
| Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS. | The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively. | |
| Heta Scanline 7D, 7AD, 7BD, 7CD and 7DD wood burning | The Instruction manual reference "Pevex1006/AH/ver2" dated June 2011. | Dry wood logs . |
| stoves. | The appliance must be fitted with permanent | |
| Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS. | stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively. | |
| Highlander 5 Clean Burn. | The manufacturer's instruction manual "Highlander. The Dunsley-Enviroburn-5. | Wood logs conforming to BS EN 13240:2001 |
| Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield, Holmfirth, West Yorkshire, HD9 3TW. | Clean Burn Stove Installation and operating instructions, D12-01-09, D060-01-09, D13-01-09, D12-12-08." | |
| Horse Flame Precision 1 model number HF905-SE. | The Instruction manual reference "HF905/UK-NI-ROI/V2.1-06-11" Dated June 2011. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Manufactured by Hi- Flame Fireplace UK Ltd, Unit 7B, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF. | The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position. | |
| Hotpod Unlimited; Hotpod Limited Edition. | The Instruction manual reference "Version 3" dated June 2011. | Wood logs . |
| Manufactured by Hotpod LLP, PO Box 137 St Ives, Cornwall, TR26 2WW. | | |
| The Hoval AgroLyt 20, 25, 35, 45 and 50. | The manufacturer's technical information and installation instructions dated January 2006, reference 4 205 194/00 and 4 205 193/00 dated | Wood logs with less than 20% moisture. |
| Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein. | June 2006. | |
| Hoval BioLyt Wood Pellet Boiler. | The Instruction manual reference "Hoval Operating Instructions, wood pellet heating boiler BioLyt (50,70,120,140,160) dated | Wood pellets . |
| Manufactured by Hoval Ltd, Northgate, Newark, Nottinghamshire, NG24 1JN. | 3/7/2008 and "Technical information assembly instructions" dated 3/10/2009. | |
| The Hoval BioLyt 50 Wood Pellet | The manufacturer's technical information and installation instructions dated October 2005, reference 4 204794/00, and operating | Wood pellets . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Boiler (49kW thermal output). | instructions dated January 2006, reference 4 204 793/01. | |
| Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein. | | |
| The Hoval BioLyt 50 and 70 models. | The manufacturer's technical information and installation instructions dated June 2007, references 4 204 794/01 and 4 204 793/02. | Wood pellets . |
| Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein. | | |
| Hoval BioLyt 160 pellet boiler. | The Instruction manual reference "Hoval Operating Instructions, wood pellet heating boiler BioLyt (50,70,120,140,160) dated | Wood pellets |
| Manufactured by Hoval Ltd, Northgate, Newark, Nottinghamshire, NG24 1JN. | 3/7/2008 and "Technical information assembly instructions" dated 3/10/2009 | |
| Hoval Forester MGS 150, 180, 240, 300, 360, 450, 550, 700, 900 boilers. | The relevant instruction manual reference "Hoval Forester MGS_MMXXXv1" (where XXX is the unit size for example 150) dated July 2011. | Wood pellets or wood chips following CEN/TS 14961. |
| Manufactured by Schmid AG, Wood firing systems PO Box 42, CH-8380 Eschikon Switzerland. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| | C. Ive | |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Hoval Forester UFS 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600. | The Instruction manual reference "Forester UFS" dated November 2009. | Wood pellets or wood chips following CEN/TS 14961. |
| Manufactured by Schmid AG, Wood firing Systems, PO Box 42, CH-8360 Eschlikon, Switzerland. | | |
| The Hoval STU 150, 200, 250, 300, 350, 425 and 500. | The manufacturer's technical information and installation instructions dated November 2007, reference STUman/01, or dated June 2008, reference STU/man/01/1. | Wood pellets . |
| Manufactured by Hoval UK Ltd, Northgate, Newark-on-Trent, Nottinghamshire, NG24 1JN. | reference of communoty is | |
| The Hoval STU 600, 800 and 1000. | The manufacturer's operating instructions dated June 2008, reference STU/man/01/1. | Wood pellets . |
| Manufactured by Hoval UK Ltd, Northgate, Newark-on-Trent, Nottinghamshire, NG24 1JN. | | |
| HSV 50 + WTH 45, 49 or 55; HSV 80 + WTH 70 or 80; HSV 100 + WTH 100. | The manufacturer's installation manual version 44 for Wood Chip and Pellet Stoves, Type HSV 30-100. Reference "BA HSV30-100 RA/RAP V44 0608". | Wood chips or wood pellets . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria. | | |
| The Huntingdon 25 clear door (model number 7057) and Huntingdon 25 tracery door (model number 7058). | The manufacturer's instruction manual, reference "PM 249 Issue 1". A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position. | Untreated dry wood . |
| Manufactured by Stovax Ltd, Falcon Road, Sowerton Industrial Estate, Exeter, Devon EX2 7LF. | | |
| The Hwam Beethoven, Hwam Beethoven H, Hwam Mozart, Hwam Ravel, Hwam Vivaldi, Hwam 30 (4.5 kW nominal thermal output). | Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference IN1 141 Ed B. The appliance must be fitted with a mechanism to prevent closure of the air wash/secondary air control | Untreated dry wood . |
| Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark. | | |
| Insert 50 Crystal. | The Instruction manual reference "6096801-Rev.17" dated 22nd December 2010. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained | No fuel is to be used |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| | and operated in accordance with the following specifications: | in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position. | |
| Insert 70. | The Instruction manual reference "6096801-Rev.17" dated 22nd December 2010. | Wood logs . |
| Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position. | |
| Insert 80 Crystal. | The Instruction manual reference "6096801-Rev.17" dated 22nd December 2010. | Wood logs . |
| Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position. | |
| Insert 100 Crystal. | The Instruction manual reference "6096801-Rev.17" dated 22nd December 2010. | Wood logs . |
| Manufactured by, LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | TOTAL CONTROL SOLVE | |
| Instyle 400; Instyle 550. | The Instruction manual reference "Instruction_manual_Instyle_1209_ENG". | Wood logs . |
| Manufactured by Dik Geurts Haardkachels BV; Industrieweg Oost 11, 6662 NE | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Elst (Gld), The Netherlands. | | |
| Italy Built In. | The Instruction manual reference "7095401 Rev.02" dated 13/12/2010. | Wood logs . |
| Manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | | |
| Italy Termo DSA; Termosuprema Compact DSA. | The Instruction manual reference "7095802 Rev.06" dated 01/02/2011. | Wood logs . |
| Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy. | | |
| Jetmaster 18f stove. | The Instruction manual reference "106870/18f/60f/Issue No.5" dated "June | Dry wood logs . |
| Manufactured by Jetmaster Fires Ltd, Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT. | 2011". | |
| Jotul F100 Stove. | The Instruction manual reference "129980" dated September 2002 and smoke control | Wood logs . |
| Manufactured by Jotul UK, Unit 1 The IOC Centre, Nash Road, Park Farm, Redditch, | area modification reference "UK F100 SC appendix" dated 2010. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | N. C. I I I. |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Worcestershire, B98 7AS. | The appliance must be fitted with a permanent stop that prevents the closure of the secondary air control beyond the 50% open position. | |
| Jydepejsen Country 510 and 760 5kW stoves. | The instruction user manual "Country001" reference "Jydepejsen A/S — June 2011" dated June 2011. | Wood logs . |
| Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.Felding, DK-7500, Holstebro, Denmark. | A permanent stop must be fitted to the secondary air control such that it cannot be closed less than 35%. | |
| KÖB Pyromat-DYN (KPM-DYN) 45, 65, 85. | The Instruction manual reference "ID 103689-L English" dated 01.01.2005 and instruction manual "ID: 103708-G English". | Wood logs (up to 0.5m) and off cuts of natural timber, wood chips and pellets. |
| Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP. | | emps and penets. |
| KÖB Pyromat-ECO (KPM-ECO) models 35, 45, 55, 65, 75, 85. | The Instruction manual reference "ID 104646-D English" dated 01.01.2005 and instruction manual "ID: 104642-B English". | Wood logs (up to 0.5m) and off cuts of natural timber. |
| Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP. | | |
| KÖB Pyromat-ECO (KPM-ECO) models 61, 81, 101, 151. | The Instruction manual reference "ID 104646-D English" dated 01.01.2005 and instruction manual "ID: 104642-B English". | Wood logs (up to 1.0m) and off cuts of natural timber. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP. | | |
| KÖB Pyrot (KRT) models 100, 150, 220, 300, 400, 540. | The Instruction manual reference "ID 104654-H English" dated 01.01.2005 and instruction manual "ID: 106811-H English". | Wood chips or wood pellets . |
| Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP. | | |
| KÖB Pyrtec (KPT) models 390, 530, 720, 950, 1250. | The Instruction manual reference "ID 104661-F English" dated 01.01.2005 and instruction manual "ID: 105174-F English". | Wood chips or wood pellets . |
| Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP. | The appliance must be fitted with multi-cyclone dedusters. | |
| Kooga Cleanburn Stove. | The Instruction manual reference "KCB 04/10A" dated April 2010. | Wood logs . |
| Manufactured by Percy Doughty & Co; Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| KOZ550, 639kW pellet boiler | The appliance must be used with a Glosfume model BMF 208 ceramic particulate filter. | 6mm diameter wood pellets . |
| Manufactured by Kayalioglu Kasabasi (Izmir-Istanbul Yolu Uzeri), PK23 Akhisar/ Manisa, Turkey. | The Green Energy Engineering Ltd (GEE) KOZ550 pellet boiler owner/operator's manual reference version 1A 2010 dated December 2010. | |
| Mansa, Tarkey. | The Glosfume Ltd maintenance and instruction manual for Glosfume BMF Biomass filter units (50 to 1000kW) version AEE001-VER4 dated December 2010. | |
| The KWB TDS Powerfire 130, 240 and 300. | The manufacturer's instructions dated 14 May 2008, reference BA TDS-05.2008, including specification of recommended fuels. | Wood pellets or wood chips . |
| Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria. | | |
| The KWB TDS Powerfire 150. | The manufacturer's instructions dated August 2005, reference BA TDS - 0805. | Wood pellets or wood chips . |
| Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH) | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria. | | |
| Lin-ka H 1500 Hot Water Boiler fitted with either a mono- cyclone (type LIN- KA 2000) or a multi- cyclone (type LIN-KA 3×2). | The Instruction manual reference "LIN-KA H 1500 Hot Water Manual/Ver. 2005/Rev. 1.10" dated 27/01/2010. | Wood pellets of maximum 8mm diameter. |
| Manufactured by LIN- KA Maskinfabrik A/ S, Nylandsvej 38, DK-6940 Lem St. Denmark. | | |
| The Little Thurlow wood burning stove. Manufactured by Town and Country Fires Pickering, North Yorkshire. | The manufacturer's instructions dated 30 June 2007, issue No. 3. | Seasoned logs of less than 20% moisture and of a maximum length of 350mm. |
| Little Wenlock Classic Wood Fuel Stove. Manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ. | The manufacturer's operating instructions dated 19 December 2008, reference N00471AXX Rev 001 DP 081219. | Dry and split wood logs of a maximum length of 25cm and a maximum diameter of 10cm. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| Lotus Liva 1, Liva 2, Liva 3 and Liva 4G stoves. | The Instruction manual "Mounting and User Instructions Lotus-Liva series Stoves" Version 4 dated January 2010. | or fuels: Wood logs . |
| Manufactured by Lotus Heating Systems A/S; Agertoften 6, 5550 Langeskov, Denmark. | | |
| Lotus Sola, Sola S, Sola M and Sola MST stoves. | The Instruction manual "Mounting and User Instructions Lotus-Sola series Stoves" Version 2 dated January 2010. | Wood logs . |
| Manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov, Denmark. | | |
| The Løvenholm. | The manufacturer's installation and operation | Untreated wood with |
| Manufactured by Hunter Stoves Ltd, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ. | manual version 07/08. | less than 20% moisture content. |
| The Løvenholm, Løvenholm Traditional, European, and Pedestal Stoves. | The manufacturer's instructions "Løvenholm Multifuel stove installation and operating manual" version 06/09. | Untreated wood with less than 20% moisture content. |
| Manufactured by Hunter Stoves Ltd, Unit 6, Old Mill | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1) (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ. | | |
| Ludlow Wood Burning Smoke Exempt Stove (Ludlow Stove SE). | The Instruction manual reference "N00529AXX REV:001" dated 13th July 2011. | Dry wood logs . |
| Manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ. | | |
| MEG 7.5/Sirius 750; MEG 4.5/Sirius 450. | The Instruction manual reference "Meg Solid Fuel Stoves Manual (107)" dated 28th January 2011. | Wood logs . |
| Manufactured Meg Stoves, F.E. Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF. | | |
| The Mescoli PB50, PB35, PB28. | The manufacturer's instruction and installation manual reference "SY315EVO P,C,B-COMBIFIRE 2 PB28/35/50 BOILERS" | Wood pellets following ÖNORM M7 135 or DIN plus |
| Manufactured by MESCOLI CALDAIE S.rI. Caldaie- Termocucine, Via del Commercio, 285 4 1058 Vignola, (MO) Italy. | Edition 1.7 Dated 1/2006. | (DIN 51731). |
| Micromet MEG 7.5 (also known as the Sirius 750); Micromet | The Instruction manual reference "Micromet Solid Fuel Stoves Manual (24)" dated 16/06/2010. | Dry wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Einanlann | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| MEG 4.5 (also known as the Sirius 450). | | |
| Manufactured by Micromet, 125 Bridge St, Birkenhead, Merseyside, CH41 1BD. | | |
| Milan Series 4. | The Instruction manual reference "CH4K Milan-V2" dated 18 November 2010. | Wood logs . |
| Manufactured by Chesney's Ltd, 194 — 200 Battersea Park Road, London, SW11 4ND. | The appliance must be fitted with a system to prevent closure of the air control beyond the 25mm open position. | |
| Milan Series 6. | The Instruction manual reference "CH6K Milan-V2" dated 18 November 2010. | Wood logs . |
| Manufactured by Chesney's Ltd, 194 — 200 Battersea Park Road, London, SW11 4ND. | The appliance must be fitted with a system to prevent closure of the air control beyond the 40mm open position. | |
| Monaco multifuel Stove, Staub Fonderie- Franco Belge model 1340605. | The Instruction manual reference "1303 - 1" dated 04/05/2010. The appliances must be fitted with a machanical stan to prevent alcours of the | Wood logs . |
| Manufactured by Staub Fonderie- Franco Belge, Rue Orphee Variscotte, BP73, 59660 Merville, France. | mechanical stop to prevent closure of the secondary air control beyond 4mm from closed. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| T | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Monfort MK2 stove. | The Instruction manual reference "1295-3" dated 17 November 2009. | Wood logs . |
| Manufactured by Franco Belge Staub, Staub Fonderie, Rue Orphee Bariscotte, BP 73, 59660 Merville, France. | The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position. | |
| Morsø-Ø4. | The Instruction manual reference "Ø—Collection" dated 01.02.2010 and instruction | Wood logs . |
| Manufactured by MORSØ UK Ltd, Unit 7 — io centre, Valley Drive, Swift Valley, Rugby, Warwickshire, CV21 1TW. | manual "72000400" dated 01.02.2010. Applies to units manufactured after 01 February 2010. | |
| The Morsø 1400 series consisting of the 1412 and 1442 models. | The manufacturer's instructions dated 10 January 2008, reference 72146800. | Wood logs with less than 20% moisture. |
| Manufactured by Morsø Jernestøberi A/ S DK-7900 Nykøbing, Mors, Denmark. | | |
| The Morsø 3100 series consisting of the 3112 and 3142 models | The manufacturer's instructions dated 4 February 2008, reference 72311200. | Wood logs with less than 20% moisture. |
| Manufactured by Morsø Jernestøberi A/ S DK-7900 Nykøbing, Mors, Denmark. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| The Morsø 6140 series consisting of the 6140 and 6148 models. | The manufacturer's instructions dated 4 September 2007, reference 72610400. | or fuels: Wood logs with less than 20% moisture. |
| Manufactured by Morsø Jernestøberi A/ S DK-7900 Nykøbing, Mors, Denmark. | | |
| Morsø Model 7600 including Model 7642, 7644 and 7648. | The instructions for installation and use 7600 reference "72762200" dated 14.07.2010. | Wood logs with less than 20% moisture. |
| Manufactured by MORSØ UK Ltd, Unit 7 — io centre, Valley Drive, Swift Valley, Rugby, Warwickshire, CV21 1TW. | The air control must have been altered such that this equates to an increased minimum open position. Reference drawings Morsø 7600-137, 7600-138, 7600-139, 7600-140 and 7600-141. | |
| The Morsø Owl 3410, 3420 and 3440 for wood burning. Manufactured by Morsø Jernestøberi A/S DK-7900 Nykøbing, Mors, Denmark. | The manufacturer's instructions dated 1 January 2000, reference 72345600. | Untreated dry wood which has been split, stacked and air dried; or air dried wood briquettes. |
| Nestor Martin C23 multifuel stove (7.7 kW), | Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1213 Edition B" and dated June 2010. | Untreated dry wood. |
| Nestor Martin C33 multifuel stove (9.2kW), | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹

⁽¹⁾

 $^{^{(1)}}$

⁽¹⁾

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Nestor Martin D33 multifuel stove (8kW). | | |
| Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Les Couvin, Belgium. | | |
| Nestor Martin "Harmony" H13 multifuel stove (3.5kW nominal thermal output). | Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1116 Edition D" and dated January 2007. | Untreated dry wood . |
| Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Les Couvin, Belgium. | | |
| Nestor Martin "Harmony" H13 multifuel stove (5kW), | Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1116 Edition D5" and dated June 2010. | Untreated dry wood . |
| Nestor Martin "Stanford" S13 multifuel stove (3.5kW). | The minimum air bleed flap must be set at a minimum of 14.5mm. | |
| Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Les Couvin, Belgium. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Nestor Martin "Harmony" H23 (6kW) and H33 (8kW) multifuel stoves. | Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1116 Edition D5" and dated June 2010. | Untreated dry wood. |
| Nestor Martin "Stanford" S23 (6kW) SP23 (6kW) S33 (8kW) and SP33 (8kW) multifuel stoves. | | |
| Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Les Couvin, Belgium. | | |
| Nestor Martin IN13 Insert multifuel stove (5 kW). | Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1214 edition B" and dated June 2010. | Untreated dry wood. |
| Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Les Couvin, Belgium. | The minimum air bleed flap must be set at a minimum of 14.5mm. | |
| Nestor Martin IT 13 multifuel stove (3.5kW). | Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1180 Edition D1" and dated June 2010. | Untreated dry wood. |
| Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Les Couvin, Belgium. | The minimum air bleed flap must be set at a minimum of 14.5mm. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Nestor Martin R23 multifuel stove (6kW). Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Les Couvin, Belgium. | Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1141 Edition B" and dated November 2006. | Untreated dry wood . |
| Nestor Martin R33 (8kW) multifuel stove. Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Les Couvin, Belgium. | Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1116 Edition D" and dated January 2007. | Untreated dry wood . |
| Newark EGTL05. Manufactured by Elite Group Trading Ltd, Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077. | The Instruction manual reference "EGTL05 Version 1.4" dated 5th July 2011. It must have factory fitting of a permanent stop to prevent any closure of the tertiary air control. | Wood logs . |
| Nørreskoven MkII. Manufactured by Hunter Stoves Ltd, Unit 6, Old Mill Industrial Estate Stoke Canon, Devon, EX5 4RJ. | The Instruction manual reference "Cleanburn, Nørreskoven MkII, Multifuel Stove. Installation and Operating Instructions, v01.11 "dated January 2011. The device must have a factory fitted stop to prevent closure of secondary air control beyond 40%. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Octoplus 10 and Octoplus 15 Boiler. Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria. | The installation instructions: Version 1.1 dated 19/04/2010; Operating manual Version 10.051 Dated 10/05/2010. | Wood pellets . |
| The ÖkoFEN Pellematic PE08, PE12, PE16, PE20, PE25, PE32, PEK12, PEK16, PEK20, PEK25, PEK32, PES12, PES16, PES20, PES25, PES32, PESK12, PESK16, PESK20, PESK25, and PESK32. | The manufacturer's instructions dated February 2007, reference PE/HB/001.E. | Wood pellets with a maximum diameter of 6mm and a maximum length of 4cm. |
| Manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark1, 4133 Niederkappel, Austria. | | |
| The ÖkoFEN Pellematic PE36, PE48, PE56, PEK36, PEK48, PEK56, PES36, PES48, PES56, PESK36, PESK48, PESK56. | The manufacturer's instructions dated March 2008, reference PBV 2000 CMP 1.4 (V2.31). | Wood pellets with a maximum diameter of 6mm and a maximum length of 4cm. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Finantaga | Conditions | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Fireplace | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark1, 4133 Niederkappel, Austria. | | |
| Olymberyl Baby Gabriel model number HF217-SE. | The Instruction manual reference "HF217-SE/UK-NI-ROI/V2.16-06-11" Dated June 2011. | Wood logs . |
| Manufactured by Hi- Flame Fireplace UK Ltd, Unit 7B, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF. | It must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position. | |
| The Orchard Ovens models: FVR Speciale 80, 100, 110, 110 × 160 and 120; TOP Superiore 100 and 120; GR 100, 120, 140, 120 × 160, 140 × 160, 140 × 180 and 180; OT 100, 120, 140, 120 × 160, 140 × 160, 140 × 160, 140 × 160, 140 × 180 and 180; the Valoriani Piccolo. | The manufacturer's instructions dated 25 October 2004, references: | Untreated dry wood . |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213 50066 Reggello, Firenze, Italy. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1)

| Fireplace | | must be installed, maintained in accordance with the cifications: and the follo | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|---------------------------------------------------------------------------------|-------------|
| | Instruction | Model | |
| | OOL inst.1 | FVR 80 | |
| | OOL inst.2 | FVR100 | |
| | OOL inst.3 | FVR 110 | |
| | OOL inst.4 | FVR 120 | |
| | OOL inst.5 | FVR 110×160 | |
| | OOL inst.6 | TOP 100 | |
| | OOL inst.7 | TOP 120 | |
| | OOL inst.8 | GR 100 and OT 100 | |
| | OOL inst.9 | GR 120 and OT 120 | |
| | OOL inst.10 | GR 140 and OT 140 | |
| | OOL inst.11 | GR 120×160 and OT 120×160 | |
| | OOL inst.12 | GR 140×160 and OT 140×160 | |
| | OOL inst.13 | GR 140×180 and OT 140×180 | |
| | OOL inst.14 | GR 180 and OT 180 | |
| | OOL inst.15 | Valoriani Piccolo | |
| Oregon EGTL03. | The Instruction manuversion 1.3" dated 5th | ual reference "EGTL03 th July 2011. | Wood logs . |
| Manufactured by Elite Group Trading Ltd, Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077. | | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | | |

| Fireplace | Conditions | |
|----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Pelle 5kW stove, Vidar Small 5kW stove and Vidar Medium 7.6kW stove. | The Instruction manual reference "8900009004" dated July 2011. | Dry wood logs . |
| Manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands. | | |
| Pelletmaster PM15, 15 kW wood pellet boiler. | The manufacturer's operating instructions for the HDG Pelletmaster 15/25 reference HDG Pelletmaster Version V1 of October 2006. | Wood pellets . |
| Manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany. | Tenenhaster version v i or october 2000. | |
| Pelletstar 10, 20, 30, 45 and 60. | The manufacturer's operating instructions dated November 2007, reference V2.2. | Wood pellets corresponding to ÖNORM M7135 of |
| Manufactured by HERZ Armaturen Ges.m.b.H, Geschäftsbereich HERZ Feuerungstechnik, A-8272 Sebersdorf 138, Austria. | | 6mm diameter . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| PelletTop 15 and PelletTop 25 Boiler. Manufactured by Solarfocus Ltd, Andreas Simetzberger, Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria. | The installation instructions: Version 020905 dated 02/09/2005. Operating manual: Version 270906 dated 27/09/2006. | Wood pellets . |
| Pevex Bohemia X30,X40, X40 Cube, X50 and X60 multifuel stoves. | The manufacturer's Instruction manual reference "AH/Ver3" and dated July 2010. | Dry wood logs |
| Manufactured by Pevex Enterprises Ltd, Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS | | |
| Pevex Bohemia X40 Inset multi-fuel appliance. | The Instruction manual reference "Pevex1004/AH/ver2/" and dated June 2011 | Dry wood logs . |
| Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS. | The appliance must be fitted with permanent stops that ensure the primary and tertiary air controls do not close beyond 0.5cm open and 2cm open positions respectively. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Pevex Serenity 40D inset multi-fuel appliance. | The Instruction manual reference "Pevex1003/AH/ver2" and dated June 2011. | Dry wood logs . |
| Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS. | The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively. | |
| Portway 1. | The Instruction manual reference: "Solid Fuel Stoves Manual issued — 20/08/2009 (291) 2". | Wood logs . |
| Manufactured by BFM Europe Ltd, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ. | The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 25mm from the left position. | |
| Portway 2; Portway 3. | The Instruction manual reference: "Solid Fuel Stoves Manual issued — 20/08/2009 (291) 2". | Wood logs . |
| Manufactured by BFM Europe Ltd, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ. | The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 20mm from the left position. | |
| Portway Inset. | The Instruction manual reference: "Solid Fuel Stoves Manual issued — 20/08/2009 (291) 2". | Wood logs . |
| Manufactured by BFM Europe Ltd, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ. | A modification of the secondary air control must be implemented such that the 20mm from left position is maintained during use. In addition the primary air control must be modified such that the minimum setting allows a bleed of air to pass through. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| • | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| The Quadra-Fire 2100 Millennium Freestanding Wood Burning Stove | The manufacturer's instructions dated 9 October 2003, reference 250-6931B. | Dry cured untreated wood of maximum size 38.1 cm × 10.16 cm × 5.08 cm . |
| Manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA | | |
| The Quadra-Fire Yosemite Freestanding Wood Burning Stove. | The manufacturer's instructions dated 4 June 2003, reference 7004-187. | Dry cured untreated wood of maximum size 38.1 cm × 10.16 cm × 5.08 cm. |
| Manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA. | | CIII ^ 3.06 CIII . |
| The Quadra-Fire Cumberland Gap Freestanding Wood Burning Stove. | The manufacturer's instructions dated 8 July 2003, reference 7006-186. | Dry cured untreated wood of maximum size 43.18 cm × 10.16 cm × 5.08 cm . |
| Manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Rais 2:1 inset stove. | The Instruction manual reference "USER MANUAL Rais 2:1 Revision 2". Dated | Wood logs . |
| Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark. | December 2009. Part number 9106510. | |
| Rais 700 inset stove. | The Instruction manual reference "USER MANUAL Rais 700 Revision 0". Dated 2010. | Wood logs . |
| Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark. | 7 | |
| Rais Epoca, Rais Poleo 95 and Rais Poleo 106 stoves. | The Instruction manual reference "USER MANUAL Rais Poleo 95 & Rais Poleo 106 Rais Epoca Revision 1". Dated December 2009. Part number 2106510. | Wood logs . |
| Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark. | 2007. Tart number 2100310. | |
| RAIS Q-Tee 57, 65 and 85. | The Instruction manual reference "Manual for RAIS Q-Tee Revision 1" dated 28th June 2011 and Supplementary instructions Rais Q-Tee | Dry wood logs . |
| Manufactured by Rais A/S Industrivej 20, | dated 7th July 2011. | |
| 9900, Frederikshavn, Denmark. | It must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position. | |
| Rais Rondo Classic and Rais Mino II stoves. | The Instruction manual reference "USER MANUAL Rais Rondo & Rais Mino II revision 2". Dated March 2008. Part number 5056510. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1)

(1)

(I)

(1)

(1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark. | | |
| Rais Rondo 92 and Rais Rondo 120 stoves. | The Instruction manual reference "USER MANUAL Rais Rondo 92 & Rais Rondo 120 revision 2". Dated December 2009. Part number 4076510. | Wood logs . |
| Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark. | | |
| Redfyre Kensal 20 flat top (product code RF-EN20M), Redfyre Kensal 33 flat top (product code RF-KEN33M and RF-KEN33W). | The manufacturer's instruction manual dated July 2008 reference PM247 issue 1, and instruction manual dated January 2009 reference PM280 issue 1. A permanent stop must be in place on the secondary air inlet to prevent closure beyond | Untreated dry wood . |
| Manufactured by Redfyre Cookers, Osprey Road, Sowton Industrial Estate, Exeter, Devon, EX2 7JG. | the 50% open position. | |
| Rika Como pellet stove. | The Instruction manual reference "IN1226 Edition 1" dated June 2011. | 6 mm wood pellets . |
| Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| - 4563 Micheldorf. Austria. | | |
| Rika Evo Aqua 9 and 15. | The Instruction manual reference "J18/HB" dated 27/02/2009. | 6mm wood pellets . |
| Manufactured by SHT Heiztechnik aus Salzburg GmbH, Rechtes Salzachufer 40 A-5101, Salzburg- Bergheim, Austria. | | |
| Rika Memo pellet stove. | The Instruction manual reference "IN1228 Edition 1" dated June 2011. | 6 mm wood pellets . |
| Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf. Austria. | | |
| Rika Pico pellet stove. | The Instruction manual reference "IN1230 Edition 1" dated June 2011. | 6 mm wood pellets . |
| Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf. Austria. | | |
| Rika Revo pellet stove. | The Instruction manual reference "IN1229 Edition 1" dated June 2011. | 6 mm wood pellets . |
| Manufactured by RIKA Innovative | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| • | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf. Austria. | | |
| Rika Topo pellet stove. | The Instruction manual reference "IN1227 Edition 1" dated June 2011. | 6 mm wood pellets. |
| Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf. Austria. | Daniel I allea valle 2011. | |
| Riva 40 Cassette 4.9kW stoves. | The Instruction manual reference "PM235 Issue 2" dated August 2009 and smoke control kit instruction manual "PM375 Issue 2" dated | Wood logs . |
| Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position. | |
| Riva 40 Freestanding, Riva 40 Avanti, Riva 40 Avanti Midi, And Riva 40 Avanti Highline 4.9kW | The Instruction manual reference "PM226 Issue 2" dated August 2009 and smoke control kit instruction manual "PM375 Issue 2" dated January 2010. | Wood logs . |
| Stoves. Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Тиерисе | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Riva 55 Cassette, Riva 66 Cassette, and Riva 66 Avanti Cassette stoves. | The Instruction manual reference "PM235 Issue 2" dated August 2009 and smoke control kit instruction manual "PM375 Issue 2" dated January 2010. | Wood logs . |
| Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate. | |
| Riva 55 Avanti Midi and Riva 66 Freestanding 8kW stoves. | The Instruction manual reference "PM226 Issue 2" dated August 2009 and smoke control kit instruction manual "PM375 Issue 2" dated January 2010. | Wood logs . |
| Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate. | |
| Riva Plus Small (5kW), Riva Plus Midi (6.5kW) and Riva Plus Medium (8 kW) stoves. | kit instruction manual "PM402 Issue 1" dated November 2009. | Wood logs . |
| Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Riva Studio 1 (5kW) freestanding wood stove. | The Instruction manual reference "PM452 Issue 1" dated June 2010 and smoke control kit instruction manual "PM400 Issue 3" dated June 2010. | Wood logs . |
| Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed. | |
| Riva Studio 2 (8kW) freestanding wood stove. | The Instruction manual reference "PM452 Issue 1" dated June 2010 and smoke control kit instruction manual "PM400 Issue 3" dated June 2010. | Wood logs . |
| Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed. | |
| Riva Studio 1 Cassette (5kW). Manufactured by | The Instruction manual reference "PM274 Issue 2" dated October 2009 and smoke control kit instruction manual "PM400 Issue 1" dated November 2009. | Wood logs . |
| Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Riva Studio 2 Cassette (8kW). Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | The Instruction manual reference "PM274 Issue 2" dated October 2009 and smoke control kit instruction manual "PM400 Issue 1" dated November 2009. A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed. | Wood logs . |
| Riva Vision Small (5kW) — Multifuel; Riva Vision Midi (6.5kW) — Multifuel. | The Instruction manual reference "PM278 Issue 2a" dated October 2009 and smoke control kit instruction manual "PM401 Issue 1" dated January 2010. | Wood logs . |
| Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position. | |
| Riva Vision Medium (8 kW) — Multifuel. Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | The Instruction manual reference "PM278 Issue 2a" dated October 2009 and smoke control kit instruction manual "PM401 Issue 1" dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position. | Wood logs . |
| Rosedale SC Multifuel Stove. | The "Rosedale Smoke Control Stove Installation and User Instructions Issue 1" dated 1 May 2010. | Wood logs with a maximum of 20% moisture. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Manufactured by Town & Country Fires Ltd, 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA. | The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position. | |
| Saltfire Oslo-Eco; Fireglow Eco 7; and Ecowarm Crystal 6. | The Instruction manual reference "ECO7operation-Revision 2A" dated 24.01.2011. | Wood logs . |
| Manufactured by Saltfire Stoves Ltd, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, BH20 4DY. | | |
| The Scan Anderson 4-5. | The manufacturer's instructions dated 15 November 2007, entitled "Scan Andersen 4-5", reference 09/05-GB. | Untreated dry wood . |
| Manufactured by Krog Iversen 7 Co., A/S DK-5492 Vissenbjerg, Denmark. | A permanent stop must be in place on the secondary air inlet to prevent closure beyond 20mm. | |
| Schmid UTSK 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600 kW. | The manufacturer's instruction manual "UTSK-ABC.22-AME-S-PPU" dated 25.09.2008 (where ABC is model number ie. 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600). | Wood pellets or wood chips following CEN/TS 14961:2005. |
| Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Schmid UTSL 30, 40, 50, 65, 80, 110, 150 kW. Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland. | The manufacturer's instruction manual reference "Operating Manual Wooden Chips and Pellets Plant. Lignumat UTSL" dated 23.12.2004. | Wood pellets or wood chips following CEN/TS 14961:2005. |
| Schmid UTSP 180, 240, 300 kW. Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon. | The manufacturer's instruction manual "UTSK - ABC22-AME-S-PPU" dated 25.09.2008 (where ABC is model number i.e. 180, 240, 300). | Wood pellets following CEN/TS 14961:2005. |
| Schmid UTSR 150, 180, 240, 300, 360, 450, 550, 700, 900 kW Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon. | The manufacturer's instruction manual "UTSR - ABC22-AME-S-PPV" dated 25.09.2008 (where ABC is model number i.e. 150, 180, 240, 300, 360, 450, 550, 700, 900). | Wood pellets or wood chips following CEN/TS 14961:2005. |
| Serrano 5, York Midi; Monterrey 6 Stoves. Manufactured by Broseley Ltd, Knights Way, | The Instruction manual reference "09TJD" dated 01 2010. A system that prevents the closure of the secondary air flaps to be less than 8mm open position must be fitted. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1

(1)

(1)

(1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Park, Shrewsbury, Shropshire, SY1 3AB. | | |
| Serrano 5 Multi Fuel and Monterrey 6 Multi Fuel Stoves. | The Instruction manual reference "TJ09C" dated 21st December 2009. | Wood logs . |
| Manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB. | The appliance must be fitted with a system that prevents the closure of the secondary air flaps to be less than 8mm open position. | |
| Serrano 7 Multi Fuel stove. | The Instruction manual reference "TJ09C" dated 21st December 2009. | Wood logs . |
| Manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB. | The appliance must be fitted with a system that prevents the closure of the secondary air flaps to be less than 10mm open position. | |
| The Stockton 3 flat top (product code 7118) Stockton 4 flat top (product code 7101 and 7102) and Stockton 5 flat top (product code 7127) Stockton 5 midline (product code 7130) Stockton 6 flat top (product codes 7100 and 7162) Stockton 6 Highline (product code 7117) and Stockton 7 | The manufacturer's instruction manual dated July 2008, reference "PM227 ENG Issue 2", and instruction manual dated January 2009, reference "PM271 Issue 2". A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position. | Untreated dry wood . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|-------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| flat top (product codes 7120 and 7163) | | |
| Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon EX2 7LF. | | |
| The Stockton 5 flat top (model number 7119) Stockton 5 Canopy (model number 7160) and Stockton 5 Midline (model number 7133). | The manufacturer's instructions reference, "PM176 — issue 4". A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position. | Untreated dry wood . |
| Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon EX2 7LF. | | |
| Stockton 7 Inset Convector (product codes 7125F and 7125C). | The manufacturer's instruction manual dated May 2008, reference "PM230 Issue 1", and instruction manual dated January 2009, reference "PM281 Issue 1". | Untreated dry wood . |
| Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon EX2 7LF. | A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Stockton Milner (4.6 kW) inset stove — smoke control version. Manufactured by | The Instruction manual reference "PM416 Issue 1" (June 2010) and smoke control kit instruction manual "PM501 Issue 1" (June 2010). | Wood logs . |
| Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position. | |
| Strebel SRP TR 90, 90 kW output pellet boiler. | The Strebel SRP TR 90 pellet boiler installation manual reference "Installation and operation instructions for special pellet-furnace" version 09:2010. | 6mm diameter wood pellets . |
| Manufactured by Strebel Ltd, 1F Albany Park Industrial Estate, Frimley Road, Camberley, Surrey, GU15 7P. | 07.2010. | |
| Stretton Insert Smoke Exempt Wood Fuel Stove (Stretton Stove SE). | The Instruction manual reference "N00530AXX REV:001" dated 12th July 2011. | Dry wood logs . |
| Manufactured by Aga, Station Road, Ketley Telford, Shropshire, TF1 5AQ. | | |
| Suprema, Mamy and Italy Hard Top. | The Instruction manual reference "7095701 Rev.09" dated 13/12/2010. | Wood logs . |
| Manufactured by La Nordica Spa, Via | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Summano 104 M. Precalcino, 36030, Vicenza, Italy. | | |
| Talbott 150-CMH 150 kW output Biomass Air Heater. | The Instruction manual for Talbott 150-CMH hand-fed Biomass Air Heater operating package reference "OM-150-CMH version.1" | Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts. |
| Manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS. | dated January 2011. | empovard officials. |
| Talbott's Automatic Biomass Air Heaters, models T1.5/A, T3/A, T5/A and TM/A. | The manufacturer's instructions reference "T/A JANUARY 1990". | Hardwood or softwood shavings or sawdust . |
| Formerly manufactured by Talbott's Heating Ltd, and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS. | | |
| Talbott's Biomass Energy Models C1, C2, C3 and C4. | The manufacturer's instructions dated August 1995 reference "Issue C1000/C/Range". | Chipboard or wood shavings, forestry chips. |
| Formerly manufactured by | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Talbott's Heating Ltd, and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS. | | |
| Talbott's model T75, T150, T300 Biomass Air Heaters. | The manufacturer's instructions dated 1st January 1995 reference — models T75, T150 and T300: "gen/sttech". | Wood offcuts, woodwaste, pellets, chipboard. |
| Formerly manufactured by Talbott's Heating Ltd, and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS. | | |
| Talbott's T500 Biomass Air heater (afterburn model). Formerly manufactured by Talbott's Heating Ltd, and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS. | The manufacturer's instructions dated January 1st 1983 reference A10000. The afterburn cycle must last not less than 25 minutes and must come into operation each time the loading door is opened. | Wood offcuts, woodwaste, pellets, chipboard. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Therminator II 22 and Therminator II 30 Boiler. | The installation instructions: "Version.:11/08/06" dated 07/2006; | Wood pellets . |
| Manufactured by Solarfocus Ltd,Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria. | Operating Manual "V8.051" dated 09/2009. Maintenance Instructions: "Ver.:01/09/06" dated 2006. | |
| Therminator II 27 and Therminator II 36 Boiler. | The installation instructions: "Version.:11/08/06" dated 07/2006; | Wood logs . |
| Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria. | Operating Manual "V8.051" dated 09/2009. Maintenance Instructions: "Ver.:01/09/06" dated 2006. | |
| Therminator II 40 Boiler. | The installation instructions: "Version.:11/08/06" dated 07/2006; | Wood pellets or wood chips . |
| Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria. | Operating Manual "V8.051" dated 09/2009. Maintenance Instructions: "Ver.:01/09/06" dated 2006. | |
| Therminator II 49 and Therminator II 60 Boiler. | The installation instructions: "Version.:11/08/06" dated 07/2006; | Wood logs or wood pellets or wood chips. |
| Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 | Operating Manual "V8.051" dated 09/2009. Maintenance Instructions: "Ver.:01/09/06" dated 2006. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| St.Ulrich, Steyr, Austria. | | |
| Thornhill T3 small. | The Instruction manual reference "ED/11/05" dated January 2011. | Wood logs . |
| Manufactured by Thornhill Eco Design Ltd:58-60 Wincheap, Canterbury, Kent, CT1 3RS. | The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm. | |
| Tiger SuperClean. Manufactured by Tiger stoves, Focus Arts & Crafts Co., Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tainjin, P. R. China 300350. | The Instruction manual reference "INSTALLATION AND OPERATING INSTRUCTIONS document v.148" dated April 2010. | Wood logs . |
| Turbhogar Alfa 80T and 65T, Turbhogar Beta 80T, Turbhogar Delta 80T and 65T, Turbhogar Lambda 80T and 65T, Turbhogar Sigma 80T and 65T, Turbhogar Omega 80T and Turbhogar Tau 80T and 65T fireplace inserts. | The manual of assembly and use reference "RR100920" dated 20/09/2010 and supplementary instruction manual reference "UK100920" dated 20/09/2010. The appliance must be fitted with a system that prevents the full closure of the air control opening so that the air openings remain 3mm (30%) open at the minimum setting. | Wood logs . |
| Manufactured by Rofer & Rodi UK Ltd, Rofer & Rodi | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| UK Ltd, Unit 10, Millennium Road, Airedale Business Centre, Skipton, North Yorkshire, BD23 2TZ. | | |
| The Twin Heat CS 150i. Manufactured by TWIN HEAT A/S, Nørrevangen 7, DK-9631 Gedsted, Denmark. | The manufacturer's operating instructions dated 17 December 2008, version 6.0.03. | Wood pellets of a maximum length of 30mm and diameter of 6mm and conforming to CEN/TS 14961:2005. |
| The Type USV wood pellet and wood chip fired boilers, model numbers USV-15, 25, 30, 40, 50, 60, 80 and 100. | The manufacturer's instructions dated August 2003, reference BA-USV 0803. | Wood pellets or wood chips . |
| Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria. | | |
| The Type USP wood pellet fired boilers, model numbers USP-10, 15, 20, 25 and 30. | The manufacturer's instructions dated 28 July 2003 reference BA-USP 0703. | Wood pellets . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| | | , |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria. | | |
| VarioWIN VA 120 12kW wood pellet boiler. Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager, Str.20, A-5201 Seerkirchen bei Salzburg, Austria. | The installation instruction manual reference "092947/00" dated 01/2010 and operating instruction manual reference "092945/00" dated 01 2010. | Wood pellets, 6mm diameter, length 80% between 15-30mm and a density of at least 1.1kg/dm3. |
| View 3 (3.8 kW) and View 5 (4.9kW) multifuel stoves; View 5 (4.9kW) wood stove. | The Instruction manual reference "PM485 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM490 Issue 1" dated June 2010. | Wood logs . |
| Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position. | |
| View 7 (7 kW) inset appliance Product code VW-7NMF. | The Instruction manual reference "PM552 — Issue 1" dated June 2011 and smoke control kit | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | N. C. lin 1 |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by Stovax Ltd: Falcon Road, Sowton | instruction manual reference "PM490 Issue 2" dated July 2011. | |
| Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position. | |
| Westcott 5SE. | The Instruction manual reference "08/51351/0 — Issue 0", dated 07/09/10. | Wood logs . |
| Manufactured by Dimplex, GDC Group Ltd, Millbrook House, Grange Drive, Hedge End Southampton, SO30 2DF. | | |
| Westfire Series One stove and Westfire Series Two stove. | The Westfire WF One and Two series installation manual and operating instructions and supplementary Instruction manual reference "Westfire supplementary instructions | Wood logs . |
| Manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark. | June 2011/Version 1" dated 1st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open. | |
| The Westfire Uniq 15, 16 and 20 (also known as WF UNIQ 15, 16 and 20). | The manufacturer's instructions dated 2007, reference WF15 — WF16 — WF20 along with supplementary instructions dated 2007, reference 01 wfuk.2207. | Untreated dry wood. |
| Manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark. | A permanent stop must be in place on the secondary air inlet to prevent closure beyond 50mm. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Westfire Uniq 18; Westfire Uniq 17; Westfire Uniq 19; Westfire Uniq 23; | The Instruction manual reference "WESTFIRE SUPPLEMENTARY INSTRUCTIONS JUNE 2010". | Wood logs . |
| Westfire Uniq 23 side Glass; Westfire Uniq 23 Inset. | The appliance must be fitted with a mechanical stop to prevent closure of the air slide beyond the 30mm open position. | |
| Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark. | | |
| Westfire Uniq 21 stove, Westfire Uniq 21 pedestal stove and Westfire Uniq 21 wall hung stove. | The Westfire WF21 installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. | Wood logs . |
| Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark. | The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 60% open. | |
| Westfire Uniq 26 stove, Westfire Uniq 27 stove and Westfire Uniq 28 stove. | The Westfire WF26, WF27, WF28 installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. | Wood logs . |
| Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark. | The appliance must be fitted with a permanent stop to the secondary air slider control to prevent closure more than 20mm from the fully closed position. | |
| Westfire Uniq 32 Inset stove and Westfire | The Westfire WF23/Uniq23, WF32/Uniq 32 inset stove installation manual and operating | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Uniq 32 Freestanding stove. Manufactured by Westfire APS, | instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. | |
| Tømrervej 3, DK-6800 Varde, Denmark. | The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open. | |
| The Windhager Bio Win 90 and 120. | The manufacturer's instructions dated August 2008, reference 092125/00. | Wood pellets . |
| Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria. | | |
| The Windhager Bio Win 100, 150, 210 and 260. | The manufacturer's instruction manual dated May 2008, reference 0916197/00. | Wood pellets . |
| Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager- Str. 20, A-5201 Seerkirchen bei Salzburg, Austria. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 100; | The Instruction manual reference "OOLinst.8 GR 100 and OT 100 v2" and dated January 2011. | Untreated wood of less than 20% moisture . |
| Wood Fired Ovens by Jamie Oliver Ltd's OT | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Valoriani Ristorante 100. | | |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 120; | The Instruction manual reference "OOLinst.9 GR 120 and OT 120 v2" and dated January 2011. | Untreated wood of less than 20% moisture. |
| Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 120. | | |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140; | The Instruction manual reference "OOLinst.10 GR 140 and OT 140 v2" and dated January 2011. | Untreated wood of less than 20% moisture. |
| Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 140. | | |
| Manufactured by Valoriani of Via Caselli alla Fornace, | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 120×160; | The Instruction manual reference "OOLinst.11 GR 120×160 and OT 120×160 v2" Dated January 2011. | Untreated wood of less than 20% moisture . |
| Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 120×160. | | |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140×160; | The Instruction manual reference "OOLinst.12 GR 140×160 and OT 140×160 v2" and dated January 2011. | Untreated wood of less than 20% moisture . |
| Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 140×160. | | |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's GR | The Instruction manual reference "OOLinst.13 GR 140×180 and OT 140×180 v2" and dated January 2011. | Untreated wood of less than 20% moisture. |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| - | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Valoriani Ristorante 140×180; | | |
| Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 140×180. | | |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 180; | The Instruction manual reference "OOLinst.14 GR 180 and OT 180 v2" and dated January 2011. | Untreated wood of less than 20% moisture. |
| Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 180. | | |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 100. | The Instruction manual reference "OOLinst.2 FVR 100 v2" and dated January 2011. | Untreated wood of less than 20% moisture. |
| Manufactured by Valoriani of Via Caselli alla Fornace, | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1)

| - | | |
|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 110. | The Instruction manual reference "OOLinst.3 FVR 110 v2" and dated January 2011. | untreated wood of less than 20% moisture. |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 110×160. | The Instruction manual reference "OOLinst.5 FVR 110×160 v2" and dated January 2011. | Untreated wood of less than 20% moisture. |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 120. | The Instruction manual reference "OOLinst.4 FVR120 v2" and dated January 2011. | Untreated wood of less than 20% moisture. |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 80. | The Instruction manual reference "OOLinst.1 FVR 80 v2" and dated January 2011. | Untreated wood of less than 20% moisture . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Piccolo. | The Instruction manual reference "OOLinst.15 Valoriani Piccolo v2" and dated January 2011. | Untreated wood of less than 20% moisture . |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Villa 100. | The Instruction manual reference "OOLinst.6 TOP 100 v2 Dated" January 2011. | Untreated wood of less than 20% moisture. |
| Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Villa 120. | The Instruction manual reference "OOLinst.7 TOP 120 v2 Dated" January 2011. | Untreated wood of less than 20% moisture. |
| Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy. | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

| Fireplace | Conditions | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Woodpecker 15, 25 and 45 wood pellet boilers. | The Instruction manual reference "Europe Issue 4" dated July 2010. | Wood pellets conforming to CEN TS 14961. |
| Formerly manufactured by Garranlea Renewables Ltd, and now manufactured by Woodpecker Energy UK, Abbey Manor, Business Centre, Preston Road, Yeovil, BA20 2FJ. | | |
| Woodpecker Thermon 200 boiler. | Instruction manual reference "Thermon Europe Issue 1" dated January 201.1 | 6mm wood pellets . |
| Manufactured by Woodpecker Energy UK, Abbey Manor, Business Centre, Preston Road, Yeovil, BA20 2FJ. | | |
| Woodpecker Thermon 250 boiler. | Instruction manual reference "Thermon Europe Issue 1" dated January 2011. | 6mm wood pellets . |
| Manufactured by Woodpecker Energy UK, Abbey Manor, Business Centre, Preston Road, Yeovil, BA20 2FJ. | | |
| Woodpecker Thermon 300 boiler. | Instruction manual reference "Thermon Europe Issue 1" dated January 2011. | 6mm wood pellets . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |
| | | |

(1)

(1)

(1)

(1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel |
|------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| Manufactured by Woodpecker Energy UK, Abbey Manor, Business Centre, Preston Road, Yeovil, BA20 2FJ. | | or fuels: |
| The Wood Waste Technology Heater, models WT10 and WT15. | The manufacturer's instructions dated 19 January 2005, reference WT10 and WT15. | Medium density fibreboard, chipboard, hardwood or softwood offcuts. |
| Manufactured by Wood Waste Technology Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ. | | |
| The Wood Waste Technology Ltd. WT5. | The manufacturer's instructions dated 16 February 2009, reference WT5_v2. | Medium density fibreboard, chipboard, hardwood or softwood |
| Manufactured by Wood Waste Technology Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ. | | offcuts. |
| WTA WT Auto 200 kW Airheater. | The Instruction manual reference "WTA Installation Operation & Maintenance Instructions" WTA v. I. Issue A. dated April | Chipboard, medium density fibreboard, softwood, hardwood. |
| Manufactured by Wood Waste | Instructions" WTA v1 Issue A dated April 2011. | All fuels to be chipped to a maximum size of |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1)

| Fireplace | Conditions | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
| Technology Ltd of Stafford, Units 1, 2 & 3, Drummond Road, Astonfields Industrial Estate, Stafford, ST16 3HJ. | | 25mm and a maximum moisture content of 20%. Maximum fines (sawdust) content 5%. |
| WTH 150 and WTH 200 boilers. Manufactured | The manufacturer's installation manual "version 91 for Large Capacity Boiler WTH 150-200. Reference BA GK V90b 0309". | Wood chips or wood pellets . |
| by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria. | | |
| Xeoos 5kW stove Versions: Natur, Style, Harmony, Pur, Classic, Elegance and Stone. | The manufacturer's "operating and installation instructions Xeoos 5k W/8kW model 2008" reference "Revisions — Index 01/08 Fassung Januar 2008". | Wood logs conforming to DIN 51731 . |
| Xeoos 8kW stove Versions: Basic, Pur, Classic, Elegance Stone and Air. | | |
| Manufactured by Specht Modulare Ofensysteme GmbH & Co, KG i.V. Dipl Ing. Frank Werner Projektmanagement Bahnhofstr, 2 D 35116 Hatzfeld | | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Yeoman CL 7 (7 kW) inset appliance Product code YM- CL7NMF. | The Instruction manual reference "PM553 — Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011. | Wood logs . |
| Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position. | |
| Yeoman CL Milner Stove Product code YM-CLMB. | The Instruction manual reference "PM559 — Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011. | Wood logs . |
| Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position. | |
| Yeoman CL3 (3.8 kW) and CL5 (4.9 kW) multifuel stoves; Yeoman CL5 (4.9 kW) wood Stove. | The Instruction manual reference "PM489 Issue 1" dated June 2010 and smoke control kit instruction manual "PM491 Issue 1" dated 5 April 2010. | Wood logs . |
| Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position. | |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

⁽¹⁾ (1) (1)

| Fireplace | Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Yeoman Devon — Multifuel, flat top, 1 door (9kW); Yeoman Devon — Multifuel, flat top, 2 door (9kW); Yeoman Devon — Multifuel, low canopy, 1 door (9kW); Yeoman Devon — Multifuel, low canopy, 2 door (9kW); Yeoman Devon — Multifuel, high canopy, 1 door (9kW); Yeoman Devon — Multifuel, high canopy, 2 door (9kW); Yeoman Devon — Multifuel, high canopy, 2 door (9kW). | The Instruction manual reference "PM184 Issue 3" dated February 2008 and smoke control kit instruction manual "PM403 Issue 1" dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and a system that ensures a gap of 1mm for bleed of primary air when the spin wheels are rotated to their closed positions must be fitted. | Wood logs . |
| Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF. | | |
| Yeoman Exmoor — Multifuel, flat top (4.9kW); Yeoman Exmoor — Multifuel, low canopy (4.9kW); Yeoman Exe — Multifuel, flat top, 1 door (4.9kW); Yeoman Exe — Multifuel, flat top, 2 door (4.9kW); Yeoman Exe — Multifuel, flat top, 2 | The Instruction manual reference "PM184 Issue 3" dated February 2008 and smoke control kit instruction manual "PM403 Issue 1" dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 60% open position and a system that prevents full closure of the primary air controls must be fitted. | Wood logs . |
| The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings. | | |

(1) (1)

| Fireplace | Conditions | | |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|--|
| | The fireplace must be installed, maintained and operated in accordance with the following specifications: | No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: | |
| low canopy, 1 door | | | |
| (4.9kW); Yeoman | | | |
| Exe — Multifuel, | | | |
| low canopy, 2 door | | | |
| (4.9kW); | | | |
| Manufactured by | | | |
| Stovax Ltd; Falcon | | | |
| Road, Sowton | | | |
| Industrial Estate, | | | |
| Exeter, Devon, EX2 | | | |
| 7LF. | | | |
| The fuel must not | | | |
| contain halogenated organic compounds | | | |
| or heavy metals as a | | | |
| result of treatment with | | | |
| wood-preservatives or coatings. | | | |

EXPLANATORY NOTE

(This note is not part of the Order)

This Order revokes and replaces with amendments the Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2011 (S.I.2011/38) (W.13).

Section 20 of the Clean Air Act 1993 ("the 1993 Act") places a general prohibition on the emission of smoke in smoke control areas.

The Welsh Ministers may, by order made under section 21 of the 1993 Act, exempt, in relation to Wales, specified classes of fireplace from the provisions of section 20, if they are satisfied that such fireplaces can be used for burning fuel other than authorised fuels without producing any smoke or a substantial quantity of smoke.

Article 2 of this Order exempts the fireplaces listed in the first column of the Schedule to this Order from the provisions of section 20 of the 1993 Act, subject to the conditions in the second and third columns of that Schedule.

The Welsh Ministers' Code of Practice on the carrying out of Regulatory Impact Assessments was considered in relation to this Order. As a result, a regulatory impact assessment has been prepared as to the likely costs and benefits of complying with this Order. A copy can be obtained from the Welsh Government, Cathays Park, Cardiff, CF10 3NQ.